

# SAFETY DATA SHEET

PE130G Epoxy Primer Grey



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : PE130G Epoxy Primer Grey

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Identified uses

Professional spray painting, near-industrial setting  
Use in coatings - Priming materials and coatings

#### Uses advised against

Not applicable.

### 1.3 Details of the supplier of the safety data sheet

Valspar b.v.  
Zuiveringweg 89  
8243 PE Lelystad  
The Netherlands  
tel: +31 (0)320 292200

**e-mail address of person responsible for this SDS** : [msds@valspar.com](mailto:msds@valspar.com)

#### National contact

GPS Automotive Lelystad  
tel: +31 (0)320 292288

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : Albania +1 703-741-5970  
Angola +1 703-741-5970  
Armenia +1 703-741-5970  
Azerbaijan +1 703-741-5970  
Bosnia and Herzegovina +1 703-741-5970  
Burkina Faso +1 703-741-5970  
Cambodia +1 703-741-5970  
Côte d'Ivoire +1 703-741-5970  
Ethiopia +1 703-741-5970  
French Polynesia +1 703-741-5970  
Georgia +1 703-741-5970  
Ghana +1 703-741-5970  
India 000-800-100-7141  
Kazakhstan +1 703-741-5970  
Kenya +1 703-741-5970  
Kosovo +1 703-741-5970  
Macedonia +1 703-741-5970  
Madagascar +1 703-741-5970  
Malta +1 703-741-5970  
Mozambique +1 703-741-5970  
Nigeria +1 703-741-5970  
Pakistan +1 703-741-5970  
Philippines +(63) 2-8395-3308 / 1-800-1-116-1020  
Serbia and Montenegro +1 703-741-5970  
Sierra Leone +1 703-741-5970  
South Africa 0-800-983-611  
Tanzania +1 703-741-5970

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

Thailand 001-800-13-203-9987  
 Togo +1 703-741-5970  
 Uganda +1 703-741-5970  
 Ukraine +(380)-947101374  
 Vietnam +(84)-444581938

### Supplier

**Telephone number** : Call: +31 (0)320 292200 (8:30AM - 5PM)  
**Hours of operation** :

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 2, H225  
 Skin Irrit. 2, H315  
 Eye Dam. 1, H318  
 Skin Sens. 1, H317  
 STOT RE 2, H373  
 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

#### Hazard pictograms



**Signal word** : Danger

**Hazard statements** : Highly flammable liquid and vapour.  
 Causes skin irritation.  
 May cause an allergic skin reaction.  
 Causes serious eye damage.  
 May cause damage to organs through prolonged or repeated exposure.  
 Toxic to aquatic life with long lasting effects.

#### Precautionary statements

**Prevention** : Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Do not breathe vapour or spray.

**Response** : Collect spillage.

**Storage** : Not applicable.

**Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazardous ingredients** : Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]; xylene; 2-methylpropan-1-ol and butan-1-ol

**Supplemental label elements** : Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

## SECTION 2: Hazards identification

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

### Special packaging requirements

**Containers to be fitted with child-resistant fastenings** : Not applicable.

**Tactile warning of danger** : Not applicable.

### 2.3 Other hazards

**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification** : None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-(1-methylethylidene)bis(4,1-phenyleneoxymethylene) bis[oxirane]	CAS: 25036-25-3	≥10 - ≤25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317	-	[1]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	≤14	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304	ATE [Dermal] = 1100 mg/kg ATE [Inhalation (gases)] = 5000 ppm	[1] [2]
trizinc bis(orthophosphate)	REACH #: 01-2119485044-40 EC: 231-944-3 CAS: 7779-90-0 Index: 030-011-00-6	≤10	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
pentan-2-one	EC: 203-528-1 CAS: 107-87-9	≤10	Flam. Liq. 2, H225 Acute Tox. 4, H302 Eye Irrit. 2, H319	ATE [Oral] = 1600 mg/kg	[1]
2-methylpropan-1-ol	REACH #: 01-2119484609-23 EC: 201-148-0 CAS: 78-83-1 Index: 603-108-00-1	≤2.7	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336	-	[1]
butan-1-ol	REACH #: 01-2119484630-38	≤2.7	Flam. Liq. 3, H226 Acute Tox. 4, H302	ATE [Oral] = 790 mg/kg	[1]

### SECTION 3: Composition/information on ingredients

ethylbenzene	EC: 200-751-6 CAS: 71-36-3 Index: 603-004-00-6	≤3	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336	ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
heptan-2-one	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≤3	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Oral] = 1600 mg/kg ATE [Inhalation (vapours)] = 16.8 mg/l	[1] [2]
zinc oxide	REACH #: 01-2119463881-32 EC: 215-222-5 CAS: 1314-13-2 Index: 030-013-00-7	≤0.96	Aquatic Acute 1, H400 Aquatic Chronic 1, H410  <b>See Section 16 for the full text of the H statements declared above.</b>	M [Acute] = 1 M [Chronic] = 1	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

## SECTION 4: First aid measures

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]. May produce an allergic reaction.

### 4.3 Indication of any immediate medical attention and special treatment needed

**Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

See toxicological information (Section 11)

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.

**Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

**Hazardous combustion products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

**Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

## SECTION 6: Accidental release measures

- 6.2 Environmental precautions** : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.
- 6.3 Methods and material for containment and cleaning up** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

- 7.1 Precautions for safe handling** : Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or watercourses.
- Information on fire and explosion protection**  
Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

#### Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

#### Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

#### Seveso Directive - Reporting thresholds

##### Danger criteria

PE130G Epoxy Primer Grey

## SECTION 7: Handling and storage

Category	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonnes	50000 tonnes
E2	200 tonnes	500 tonnes

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
xylene	<b>EU OEL (Europe, 1/2022) [xylene, mixed isomers]</b> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m <sup>3</sup> . STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m <sup>3</sup> .
ethylbenzene	<b>EU OEL (Europe, 1/2022)</b> Absorbed through skin. TWA 8 hours: 100 ppm. TWA 8 hours: 442 mg/m <sup>3</sup> . STEL 15 minutes: 200 ppm. STEL 15 minutes: 884 mg/m <sup>3</sup> .
heptan-2-one	<b>OEL Reference is obsolete or not recognized. Consider revising. (Europe)</b> CEIL: 50 ppm. CEIL: 233 mg/m <sup>3</sup> . <b>EU OEL (Europe, 1/2022)</b> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 238 mg/m <sup>3</sup> . STEL 15 minutes: 100 ppm. STEL 15 minutes: 475 mg/m <sup>3</sup> .

#### Biological exposure indices

No exposure indices known.

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### DNELs/DMELs

Product/ingredient name

Result

**SECTION 8: Exposure controls/personal protection**

xylene

**DNEL - General population - Consumers - Short term - Inhalation**

174 mg/m<sup>3</sup>

Effects: Local

**DNEL - General population - Consumers - Short term - Inhalation**

174 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - General population - Long term - Oral**

5 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Long term - Inhalation**

65.3 mg/m<sup>3</sup>

Effects: Local

**DNEL - General population - Long term - Inhalation**

65.3 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - General population - Long term - Dermal**

125 mg/kg bw/day

Effects: Systemic

**DNEL - Workers - Long term - Dermal**

212 mg/kg bw/day

Effects: Systemic

**DNEL - Workers - Long term - Inhalation**

221 mg/m<sup>3</sup>

Effects: Local

**DNEL - Workers - Long term - Inhalation**

221 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - General population - Short term - Inhalation**

260 mg/m<sup>3</sup>

Effects: Local

**DNEL - General population - Short term - Inhalation**

260 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Short term - Inhalation**

442 mg/m<sup>3</sup>

Effects: Local

**DNEL - Workers - Short term - Inhalation**

442 mg/m<sup>3</sup>

Effects: Systemic

pentan-2-one

**DNEL - General population - Long term - Oral**

15.19 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Long term - Dermal**

15.19 mg/kg bw/day

Effects: Systemic

**SECTION 8: Exposure controls/personal protection**

	<p><b>DNEL - Workers - Long term - Dermal</b>                  20.18 mg/kg bw/day  <u>Effects:</u> Systemic</p> <p><b>DNEL - General population - Long term - Inhalation</b>                  52.84 mg/m<sup>3</sup>  <u>Effects:</u> Systemic</p> <p><b>DNEL - Workers - Long term - Inhalation</b>                  212.42 mg/m<sup>3</sup>  <u>Effects:</u> Systemic</p> <p><b>DNEL - General population - Short term - Inhalation</b>                  264.2 mg/m<sup>3</sup>  <u>Effects:</u> Systemic</p> <p><b>DNEL - Workers - Short term - Inhalation</b>                  1062.1 mg/m<sup>3</sup>  <u>Effects:</u> Systemic</p>
2-methylpropan-1-ol	<p><b>DNEL - General population - Long term - Oral</b>                  25 mg/kg bw/day  <u>Effects:</u> Systemic</p> <p><b>DNEL - Workers - Long term - Inhalation</b>                  310 mg/m<sup>3</sup>  <u>Effects:</u> Systemic</p> <p><b>DNEL - General population - Long term - Inhalation</b>                  55 mg/m<sup>3</sup>  <u>Effects:</u> Local</p> <p><b>DNEL - Workers - Long term - Inhalation</b>                  310 mg/m<sup>3</sup>  <u>Effects:</u> Local</p>
butan-1-ol	<p><b>DNEL - General population - Consumers - Long term - Dermal</b>                  3.125 mg/kg bw/day  <u>Effects:</u> Systemic</p> <p><b>DNEL - General population - Long term - Oral</b>                  1.5625 mg/kg bw/day  <u>Effects:</u> Systemic</p> <p><b>DNEL - General population - Long term - Dermal</b>                  3.125 mg/kg bw/day  <u>Effects:</u> Systemic</p> <p><b>DNEL - General population - Long term - Inhalation</b>                  55.357 mg/m<sup>3</sup>  <u>Effects:</u> Systemic</p> <p><b>DNEL - General population - Long term - Inhalation</b>                  155 mg/m<sup>3</sup>  <u>Effects:</u> Local</p> <p><b>DNEL - Workers - Long term - Inhalation</b>                  310 mg/m<sup>3</sup>  <u>Effects:</u> Local</p>
ethylbenzene	<p><b>DMEL - Workers - Long term - Inhalation</b></p>

**SECTION 8: Exposure controls/personal protection**

442 mg/m<sup>3</sup>  
Effects: Local

**DMEL - Workers - Short term - Inhalation**  
 884 mg/m<sup>3</sup>  
Effects: Systemic

**DNEL - General population - Long term - Oral**  
 1.6 mg/kg bw/day  
Effects: Systemic

**DNEL - General population - Long term - Inhalation**  
 15 mg/m<sup>3</sup>  
Effects: Systemic

**DNEL - Workers - Long term - Inhalation**  
 77 mg/m<sup>3</sup>  
Effects: Systemic

**DNEL - Workers - Long term - Dermal**  
 180 mg/kg bw/day  
Effects: Systemic

**DNEL - Workers - Short term - Inhalation**  
 293 mg/m<sup>3</sup>  
Effects: Local

heptan-2-one

**DNEL - General population - Long term - Oral**  
 23.32 mg/kg bw/day  
Effects: Systemic

**DNEL - General population - Long term - Dermal**  
 23.32 mg/kg bw/day  
Effects: Systemic

**DNEL - Workers - Long term - Dermal**  
 54.27 mg/kg bw/day  
Effects: Systemic

**DNEL - General population - Long term - Inhalation**  
 84.31 mg/m<sup>3</sup>  
Effects: Systemic

**DNEL - Workers - Long term - Inhalation**  
 394.25 mg/m<sup>3</sup>  
Effects: Systemic

**DNEL - Workers - Short term - Inhalation**  
 1516 mg/m<sup>3</sup>  
Effects: Systemic

zinc oxide

**DNEL - General population - Long term - Dermal**  
 83 mg/kg bw/day  
Effects: Systemic

**DNEL - General population - Long term - Inhalation**  
 2.5 mg/m<sup>3</sup>  
Effects: Systemic

**DNEL - Workers - Long term - Dermal**  
 83 mg/kg bw/day  
Effects: Systemic

**SECTION 8: Exposure controls/personal protection**

**DNEL - Workers - Long term - Inhalation**

5 mg/m<sup>3</sup>

Effects: Systemic

**PNECs**

**Product/ingredient name**

xylene

**Result**

**Fresh water**

0.327 mg/l

**Marine water**

0.327 mg/l

**Sewage Treatment Plant**

6.58 mg/l

**Fresh water sediment**

12.46 mg/kg dwt

**Marine water sediment**

12.46 mg/kg dwt

**Soil**

2.31 mg/kg dwt

trizinc bis(orthophosphate)

**Fresh water**

20.6 µg/l

**Marine water**

6.1 µg/l

**Sewage Treatment Plant**

100 µg/l

**Fresh water sediment**

117.8 mg/kg dwt

**Marine water sediment**

56.5 mg/kg dwt

**Soil**

35.6 mg/kg dwt

pentan-2-one

**Fresh water**

0.11 mg/l

**Marine water**

0.011 mg/l

**Sewage Treatment Plant**

0.25 mg/l

**Fresh water sediment**

0.717 mg/kg dwt

**Marine water sediment**

0.072 mg/kg dwt

**Soil**

0.079 mg/kg dwt

2-methylpropan-1-ol

**Fresh water - Assessment Factors**

0.4 mg/l

**SECTION 8: Exposure controls/personal protection**

	<p><b>Marine - Assessment Factors</b> 0.04 mg/l</p> <p><b>Sewage Treatment Plant - Assessment Factors</b> 10 mg/l</p> <p><b>Fresh water sediment - Equilibrium Partitioning</b> 1.56 mg/kg dwt</p> <p><b>Marine water sediment - Equilibrium Partitioning</b> 0.156 mg/kg dwt</p> <p><b>Soil - Equilibrium Partitioning</b> 0.076 mg/kg dwt</p>
butan-1-ol	<p><b>Fresh water - Assessment Factors</b> 0.082 mg/l</p> <p><b>Marine water - Assessment Factors</b> 0.0082 mg/l</p> <p><b>Sewage Treatment Plant - Assessment Factors</b> 2476 mg/l</p> <p><b>Fresh water sediment - Equilibrium Partitioning</b> 0.324 mg/kg dwt</p> <p><b>Marine water sediment - Equilibrium Partitioning</b> 0.0324 mg/kg dwt</p> <p><b>Soil - Equilibrium Partitioning</b> 0.017 mg/kg dwt</p>
ethylbenzene	<p><b>Fresh water</b> 0.1 mg/l</p> <p><b>Marine water</b> 0.01 mg/l</p> <p><b>Sewage Treatment Plant</b> 9.6 mg/l</p> <p><b>Fresh water sediment</b> 13.7 mg/kg dwt</p> <p><b>Marine water sediment</b> 1.37 mg/kg dwt</p> <p><b>Soil</b> 2.68 mg/kg dwt</p>
heptan-2-one	<p><b>Fresh water</b> 0.0982 mg/l</p> <p><b>Marine water</b> 0.00982 mg/l</p> <p><b>Sewage Treatment Plant</b> 12.5 mg/l</p> <p><b>Fresh water sediment</b> 1.89 mg/kg dwt</p>

## SECTION 8: Exposure controls/personal protection

zinc oxide	<b>Marine water sediment</b> 0.189 mg/kg dwt
	<b>Soil</b> 0.321 mg/kg dwt
	<b>Fresh water</b> 20.6 µg/l
	<b>Marine water</b> 6.1 µg/l
	<b>Fresh water sediment</b> 117 mg/kg dwt
	<b>Sewage Treatment Plant</b> 52 µg/l
	<b>Marine water sediment</b> 56.5 mg/kg dwt
	<b>Soil</b> 35.6 mg/kg dwt

### 8.2 Exposure controls

**Appropriate engineering controls** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

#### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Use safety eyewear designed to protect against splash of liquids. chemical splash goggles and/or face shield.

#### Skin protection

##### Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

**Gloves** : For prolonged or repeated handling, use the following type of gloves:

Recommended: Recommended EN 374 fluor rubber foil  $\geq 0.7$  mm

Not recommended: Conditionally suitable materials for protective gloves; EN 374: Nitrile rubber - NBR ( $\geq 0.35$  mm). Only suitable as splash protection. Only suitable for brief exposure. In the event of contamination, change protective gloves immediately.

## SECTION 8: Exposure controls/personal protection

The recommendation for the type or types of glove to use when handling this product is based on information from the following source:

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

- Body protection** : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.  
Cotton or cotton/synthetic overalls or coveralls are normally suitable.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

EN 405:2001 + A1:2009 organic vapour (Type A) and particulate filter FFA2P3 R D

- Environmental exposure controls** : Do not allow to enter drains or watercourses.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : Grey.
- Odour** : Characteristic.
- Odour threshold** : Not available.
- Melting point/freezing point** : Not applicable.
- Boiling point or initial boiling point and boiling range** : >100°C (>212°F)
- Flammability** : Not available.
- Lower and upper explosion limit** : Lower: 0.8%  
Upper: 11.3%
- Flash point** : Closed cup: 18.5°C (65.3°F)
- Auto-ignition temperature** : 355°C (671°F)
- Decomposition temperature** : Not applicable.
- pH** : Not applicable.
- Viscosity** : Dynamic (room temperature): Not available.  
Kinematic (room temperature): Not available.  
Kinematic (40°C): >20.5 mm<sup>2</sup>/s

**Solubility** :

Media	Result
cold water	Not soluble
hot water	Not soluble

**Solubility in water** : Not applicable.

**Partition coefficient n-octanol/water (log Pow)** : Not applicable.

**SECTION 9: Physical and chemical properties**

<b>Vapour pressure</b>	: 2 kPa (15 mm Hg)
<b>Relative density</b>	: 1.46 to 1.54
<b>Density</b>	: 1.46 to 1.54 g/cm <sup>3</sup>
<b>Relative vapour density</b>	: 3.5 [Air = 1]
<b>Particle characteristics</b>	
<b>Median particle size</b>	: Not applicable.

**9.2 Other information****9.2.1 Information with regard to physical hazard classes**

<b>Explosive properties</b>	: Not available.
<b>Oxidising properties</b>	: Not available.

**9.2.2 Other safety characteristics**

<b>Miscible with water</b>	: No.
<b>Evaporation rate</b>	: 1.6 (butyl acetate = 1)

**SECTION 10: Stability and reactivity**

<b>10.1 Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>10.2 Chemical stability</b>	: Stable under recommended storage and handling conditions (see Section 7).
<b>10.3 Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>10.4 Conditions to avoid</b>	: When exposed to high temperatures may produce hazardous decomposition products.
<b>10.5 Incompatible materials</b>	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
<b>10.6 Hazardous decomposition products</b>	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]. May produce an allergic reaction.

**Acute toxicity**

**SECTION 11: Toxicological information****Product/ingredient name**

Phenol, 4,4'-(1-methylethylidene)bis-,  
polymer with 2,2'-[(1-methylethylidene)bis  
(4,1-phenyleneoxymethylene)]bis[oxirane]

**Result****Rat - Oral - LD50**

&gt;2000 mg/kg

**Rat - Dermal - LD50**

&gt;2000 mg/kg

xylene

**Rabbit - Dermal - LD50**

12126 mg/kg

**Rat - Oral - LD50**

4300 mg/kg

**Rat - Male - Inhalation - LC50 Vapour**

29000 mg/l [4 hours]

**Rat - Inhalation - LC50 Gas.**

5000 ppm [4 hours]

trizinc bis(orthophosphate)

**Rat - Oral - LD50**

&gt;5000 mg/kg

**Rat - Inhalation - LC50 Dusts and mists**

&gt;5.7 mg/l [4 hours]

pentan-2-one

**Rabbit - Dermal - LD50**

6500 mg/kg

**Rat - Oral - LD50**

1600 mg/kg

2-methylpropan-1-ol

**Rabbit - Dermal - LD50**

3392 mg/kg

OECD [Acute Dermal Toxicity]

**Rat - Oral - LD50**

2460 mg/kg

**Rat - Inhalation - LC50 Vapour**19200 mg/m<sup>3</sup> [4 hours]

butan-1-ol

**Rat - Oral - LD50**

790 mg/kg

Toxic effects: Liver - Fatty liver degeneration  
Kidney, Ureter, and Bladder - Other changes  
Blood - Other changes

**Rabbit - Dermal - LD50**

3400 mg/kg

**Rat - Inhalation - LC50 Vapour**24000 mg/m<sup>3</sup> [4 hours]

ethylbenzene

**Rabbit - Dermal - LD50**

12126 mg/kg

**Rat - Oral - LD50**

3500 mg/kg

Toxic effects: Liver - Other changes  
Kidney, Ureter, and Bladder - Other changes

**Rat - Inhalation - LC50 Vapour**

6350 ppm [4 hours]

## SECTION 11: Toxicological information

heptan-2-one	<p><b>Rat - Oral - LD50</b> 1600 mg/kg <u>Toxic effects:</u> Behavioral - Ataxia Lung, Thorax, or Respiration - Respiratory depression</p> <p><b>Rat - Dermal - LD50</b> &gt;2000 mg/kg</p> <p><b>Rat - Inhalation - LC50 Vapour</b> 16.8 mg/l [4 hours]</p>
zinc oxide	<p><b>Rat - Dermal - LD50</b> &gt;2000 mg/kg</p> <p><b>Rat - Oral - LD50</b> &gt;5000 mg/kg</p> <p><b>Rat - Inhalation - LC50 Dusts and mists</b> &gt;5.7 mg/l [4 hours]</p>

**Conclusion/Summary [Product]** : Not available.

### Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
PE130G Epoxy Primer Grey	11230.1	9425.5	42843.2	319.2	N/A
xylene	4300	1100	5000	29000	N/A
pentan-2-one	1600	6500	N/A	N/A	N/A
2-methylpropan-1-ol	2460	3392	N/A	N/A	N/A
butan-1-ol	790	3400	N/A	24	N/A
ethylbenzene	3500	12126	N/A	11	N/A
heptan-2-one	1600	N/A	N/A	16.8	N/A

### Skin corrosion/irritation

#### Product/ingredient name

xylene

#### Result

##### Rat - Skin - Mild irritant

Duration of treatment/exposure: 8 hours

Amount/concentration applied: 60 uL

##### Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

##### Rabbit - Skin - Moderate irritant

Amount/concentration applied: 100 %

pentan-2-one

##### Rabbit - Skin - Mild irritant

Amount/concentration applied: 405 mg

butan-1-ol

##### Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 20 mg

ethylbenzene

##### Rabbit - Skin - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 15 mg

## SECTION 11: Toxicological information

heptan-2-one

**Rabbit - Skin - Mild irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 14 mg

zinc oxide

**Rabbit - Skin - Mild irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 milligrams

**Conclusion/Summary [Product]** : Not available.

### Serious eye damage/eye irritation

#### **Product/ingredient name**

xylene

#### **Result**

**Rabbit - Eyes - Mild irritant**

Amount/concentration applied: 87 mg

**Rabbit - Eyes - Severe irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 5 mg

butan-1-ol

**Rabbit - Eyes - Severe irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 2 mg

**Rabbit - Eyes - Severe irritant**

Amount/concentration applied: 0.005 MI

**Rabbit - Eyes - Severe irritant**

Amount/concentration applied: 1.62 mg

ethylbenzene

**Rabbit - Eyes - Severe irritant**

Amount/concentration applied: 500 mg

zinc oxide

**Rabbit - Eyes - Mild irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 milligrams

**Conclusion/Summary [Product]** : Not available.

### Respiratory corrosion/irritation

Not available.

**Conclusion/Summary [Product]** : Not available.

### Respiratory or skin sensitization

Not available.

### **Skin**

**Conclusion/Summary [Product]** : Not available.

### **Respiratory**

**Conclusion/Summary [Product]** : Not available.

### Germ cell mutagenicity

Not available.

## SECTION 11: Toxicological information

**Conclusion/Summary [Product]** : Not available.

### Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

Not available.

**Conclusion/Summary [Product]** : Not available.

### Reproductive toxicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Specific target organ toxicity (single exposure)

<b>Product/ingredient name</b>	<b>Result</b>
xylene	STOT SE 3, H335 (Respiratory tract irritation)
2-methylpropan-1-ol	STOT SE 3, H335 (Respiratory tract irritation)
	STOT SE 3, H336 (Narcotic effects)
butan-1-ol	STOT SE 3, H335 (Respiratory tract irritation)
	STOT SE 3, H336 (Narcotic effects)
heptan-2-one	STOT SE 3, H336 (Narcotic effects)

### Specific target organ toxicity (repeated exposure)

<b>Product/ingredient name</b>	<b>Result</b>
xylene	STOT RE 2, H373
ethylbenzene	STOT RE 2, H373 (hearing organs)

### Aspiration hazard

<b>Product/ingredient name</b>	<b>Result</b>
xylene	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1

### Information on likely routes of exposure

Not available.

### Potential acute health effects

<b>Eye contact</b>	: Causes serious eye damage.
<b>Inhalation</b>	: No known significant effects or critical hazards.
<b>Skin contact</b>	: Causes skin irritation. May cause an allergic skin reaction.
<b>Ingestion</b>	: No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

<b>Eye contact</b>	: Adverse symptoms may include the following: pain watering redness
<b>Inhalation</b>	: No specific data.
<b>Skin contact</b>	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
<b>Ingestion</b>	: Adverse symptoms may include the following: stomach pains

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

## SECTION 11: Toxicological information

### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

**Conclusion/Summary [Product]** : Not available.

**General** : May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : No known significant effects or critical hazards.

## 11.2 Information on other hazards

### 11.2.1 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

There are no data available on the mixture itself.  
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

#### Product/ingredient name

xylene

#### Result

##### Acute - EC50

Algae  
1 to 10 mg/l [72 hours]

##### Acute - LC50 - Marine water

Crustaceans - Daggerblade grass shrimp - *Palaemon pugio*  
8500 µg/l [48 hours]  
Effect: Mortality

##### Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas*  
Age: 31 days; Size: 18.4 mm; Weight: 0.077 g  
13.4 mg/l [96 hours]  
Effect: Mortality

trizinc bis(orthophosphate)

##### Acute - EC50

Mortality  
Daphnia - *Daphnia magna*  
63.1 mg/l [48 hours]

##### Acute - LC50 - Fresh water

## SECTION 12: Ecological information

	<p>Fish - Rainbow trout,donaldson trout - <i>Oncorhynchus mykiss</i>  <u>Age</u>: 180 days; <u>Weight</u>: 1.5 g                      90 µg/l [96 hours]  <u>Effect</u>: Mortality</p>
pentan-2-one	<p><b>Acute - LC50 - Fresh water</b>                      Fish - Fathead minnow - <i>Pimephales promelas</i>  <u>Age</u>: 32 days; <u>Size</u>: 18.4 mm; <u>Weight</u>: 0.095 g                      1240 mg/l [96 hours]  <u>Effect</u>: Mortality</p>
2-methylpropan-1-ol	<p><b>Acute - EC50</b>                      Algae - <i>Pseudokirchneriella subcapitata</i>                      1799 mg/l [72 hours]</p> <p><b>Chronic - NOEC</b>                      OECD [Alga, Growth Inhibition Test]                      Algae - <i>Pseudokirchneriella subcapitata</i>                      117 mg/l [72 hours]</p> <p><b>Acute - LC50 - Fresh water</b>                      Fish - Rainbow trout,donaldson trout - <i>Oncorhynchus mykiss</i>  <u>Weight</u>: 1.67 g                      1330 mg/l [96 hours]  <u>Effect</u>: Mortality</p> <p><b>Acute - LC50 - Marine water</b>                      Crustaceans - Brine shrimp - <i>Artemia salina</i>                      600 mg/l [48 hours]  <u>Effect</u>: Mortality</p> <p><b>Chronic - NOEC - Fresh water</b>                      Daphnia - Water flea - <i>Daphnia magna</i>  <u>Age</u>: ≤24 hours                      4 mg/l [21 days]  <u>Effect</u>: Reproduction</p>
butan-1-ol	<p><b>Acute - LC50</b>                      OECD [Fish, Acute Toxicity Test]                      Fish - <i>Pimephales promelas</i>                      1376 mg/l [96 hours]</p> <p><b>Acute - EC50</b>                      OECD [Daphnia sp. Acute Immobilization Test and Reproduction Test]                      Daphnia - <i>Daphnia magna</i>                      1328 mg/l [48 hours]</p> <p><b>Acute - EC50</b>                      OECD [Alga, Growth Inhibition Test]                      Algae - <i>Desmodesmus subspicatus</i>                      225 mg/l [96 hours]</p> <p><b>Chronic - NOEC</b>                      OECD [Daphnia Magna Reproduction Test]                      Daphnia - <i>Daphnia magna</i>                      4.1 mg/l [21 days]</p>
ethylbenzene	<p><b>Acute - LC50 - Fresh water</b>                      Fish - Rainbow trout,donaldson trout - <i>Oncorhynchus mykiss</i>                      4200 µg/l [96 hours]  <u>Effect</u>: Mortality</p>

## SECTION 12: Ecological information

### Acute - EC50 - Fresh water

Daphnia - Water flea - *Daphnia magna* - Neonate

Age: ≤24 hours

2.93 mg/l [48 hours]

Effect: Intoxication

### Acute - EC50 - Fresh water

Algae - Green algae - *Raphidocelis subcapitata*

3600 µg/l [96 hours]

Effect: Population

heptan-2-one

### Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas*

Age: 32 days; Size: 18.4 mm; Weight: 0.095 g

131 mg/l [96 hours]

Effect: Mortality

zinc oxide

### Acute - EC50

Algae - *Selenastrum capricornutum*

0.17 mg/l [72 hours]

### Acute - LC50

Fish - *Lepomis macrochirus*

320 ppm [96 hours]

### Chronic - NOEC

Algae - *Pseudokirchneriella subcapitata*

0.017 mg/l [72 hours]

**Conclusion/Summary [Product]** : Not available.

## 12.2 Persistence and degradability

### Product/ingredient name

2-methylpropan-1-ol

### Result

70 to 80% [28 days]

butan-1-ol

OECD [ Ready Biodegradability - Modified OECD Screening Test]

>70% [19 days]

heptan-2-one

69% [28 days] - Readily

**Conclusion/Summary [Product]** : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2-methylpropan-1-ol	-	-	Readily
butan-1-ol	-	-	Readily
heptan-2-one	-	-	Readily

## 12.3 Bioaccumulative potential

## SECTION 12: Ecological information

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bis[oxirane]	2.64 to 3.78	31	Low
xylene	3.12	8.1 to 25.9	Low
trizinc bis(orthophosphate)	-	60960	High
pentan-2-one	0.91	-	Low
2-methylpropan-1-ol	1	-	Low
butan-1-ol	1	-	Low
ethylbenzene	3.6	-	Low
heptan-2-one	2.26	-	Low
zinc oxide	-	28960	High

### 12.4 Mobility in soil

#### Soil/water partition coefficient

Product/ingredient name	logK <sub>oc</sub>	K <sub>oc</sub>
pentan-2-one	1.28	19.0784
2-methylpropan-1-ol	1.08	12.0246
butan-1-ol	0.51	3.22078
ethylbenzene	2.23	170.406
heptan-2-one	1.6	39.9018

#### Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bis[oxirane]	No	No	No	No	No	No	No
xylene	No	No	No	No	No	No	No
trizinc bis(orthophosphate)	No	No	No	No	No	No	No
pentan-2-one	No	No	No	No	No	No	No
2-methylpropan-1-ol	No	No	No	No	No	No	No
butan-1-ol	No	No	No	No	No	No	No
ethylbenzene	No	No	No	No	No	No	No
heptan-2-one	No	No	No	No	No	No	No
zinc oxide	No	No	No	No	No	No	No

**Mobility** : Not available.

**Conclusion/Summary** : The product does not meet the criteria to be considered as a PMT or vPvM.

### 12.5 Results of PBT and vPvB assessment

#### Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bis[oxirane]	No	No	No	No	No	No	No
xylene	No	No	No	No	No	No	No
trizinc bis(orthophosphate)	No	No	No	No	No	No	No
pentan-2-one	No	No	No	No	No	No	No
2-methylpropan-1-ol	No	No	No	No	No	No	No

## SECTION 12: Ecological information

butan-1-ol	No	No	No	No	No	No	No
ethylbenzene	No	No	No	No	No	No	No
heptan-2-one	No	No	No	No	No	No	No
zinc oxide	No	No	No	No	No	No	No

### Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bis[oxirane]	No	No	No	No	No	No	No
xylene	No	No	No	No	No	No	No
trizinc bis(orthophosphate)	No	No	No	No	No	No	No
pentan-2-one	No	No	No	No	No	No	No
2-methylpropan-1-ol	No	No	No	No	No	No	No
butan-1-ol	No	No	No	No	No	No	No
ethylbenzene	No	No	No	No	No	No	No
heptan-2-one	No	No	No	No	No	No	No
zinc oxide	No	No	No	No	No	No	No

**Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP]** : The product does not meet the criteria to be considered as a PBT or vPvB.

### 12.6 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

**Disposal considerations** : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

#### European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

## SECTION 13: Disposal considerations

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

### Packaging





**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

Type of packaging	European waste catalogue (EWC)
CEPE Guidelines	15 01 10* packaging containing residues of or contaminated by hazardous substances

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	Paint
14.3 Transport hazard class(es)	3 	3 	3 	3 
14.4 Packing group	II	II	II	II
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.

### Additional information

**ADR/RID** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.

**Hazard identification number** 33

**Limited quantity** 5 L

**Special provisions** 163, 640C, 650, 367

**Tunnel code** (D/E)

**ADN** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.

**Special provisions** 163, 367, 640C, 650

**IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

**Emergency schedules** F-E, \_S-E\_

**Special provisions** 163, 367

## SECTION 14: Transport information

**IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.  
**Quantity limitation** Passenger and Cargo Aircraft: 5 L. Packaging instructions: 353. Cargo Aircraft Only: 60 L. Packaging instructions: 364. Limited Quantities - Passenger Aircraft: 1 L. Packaging instructions: Y341.  
**Special provisions** A3, A72, A192

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments** : Not available.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV

None of the components are listed above the relevant limit.

###### Substances of very high concern

None of the components are listed above the relevant limit.

##### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
PE130G Epoxy Primer Grey	≥90	3
toluene	≤0.1	48
benzene	<0.1	5
		72
Nickel	≤0.1	27

**Labelling** : Not applicable.

#### Other EU regulations

**VOC** : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

**VOC for Ready-for-Use Mixture** : 2004/42/EC - IIB/c: 540 g/l (2007). ≤ 535 g/l VOC.

**Industrial emissions (integrated pollution prevention and control) - Air** : Not listed

**Industrial emissions (integrated pollution prevention and control) - Water** : Not listed

**Explosive precursors** : Not applicable.

#### Ozone depleting substances (EU 2024/590)

Not listed.

#### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

#### Persistent Organic Pollutants

## SECTION 15: Regulatory information

Not listed.

### Seveso Directive

This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.

### National regulations

**Industrial use** : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

### Inventory list

**Australia** : All components are listed or exempted.  
**Canada** : All components are listed or exempted.  
**China** : All components are listed or exempted.  
**Eurasian Economic Union** : **Russian Federation inventory**: Not determined.  
**Japan** : **Japan inventory (CSCL)**: Not determined.  
**Japan inventory (ISHL)**: Not determined.  
**New Zealand** : All components are listed or exempted.  
**Philippines** : All components are listed or exempted.  
**Republic of Korea** : All components are listed or exempted.  
**Taiwan** : All components are listed or exempted.  
**Thailand** : Not determined.  
**Turkey** : Not determined.  
**United States** : Not determined.  
**Viet Nam** : Not determined.

**15.2 Chemical safety assessment** : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

**CEPE code** : 1

Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway  
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
 ATE = Acute Toxicity Estimate  
 B = Bioaccumulative  
 BCF = Bioconcentration Factor

## SECTION 16: Other information

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
 DMEL = Derived Minimal Effect Level  
 DNEL = Derived No Effect Level  
 EUH statement = CLP-specific Hazard statement  
 IATA = International Air Transport Association  
 IMDG = International Maritime Dangerous Goods  
 IMO = International Maritime Organization  
 M = Mobile  
 N/A = Not available  
 P = Persistent  
 PBT = Persistent, Bioaccumulative and Toxic  
 PMT = Persistent, Mobile and Toxic  
 PNEC = Predicted No Effect Concentration  
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
 RRN = REACH Registration Number  
 SGG = Segregation Group  
 T = Toxic  
 vB = Very Bioaccumulative  
 vM = Very Mobile  
 vP = Very Persistent  
 vPvB = Very Persistent and Very Bioaccumulative  
 vPvM = Very Persistent and Very Mobile

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 2, H373 Aquatic Chronic 2, H411	On basis of test data Calculation method Calculation method Calculation method Calculation method Calculation method

### Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

### Full text of classifications [CLP/GHS]

## SECTION 16: Other information

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

**Date of printing** : 3/31/2025  
**Date of issue/ Date of revision** : 3/31/2025  
**Date of previous issue** : No previous validation  
**Version** : 1

### Notice to reader

The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.

# SUMI

## Safe Use of Mixtures

### Information for end-users



**Title** : Professional spray painting, near-industrial setting

*This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.*

## General description of the process covered

Indoor spray painting by professionals with efficient ventilation such as spray booth or local exhaust ventilation

## Operational conditions

**Place of use** : Indoor use

## Risk management measures (RMM)

Contributing activity	Process category (ies)	Maximum duration	Ventilation	
			Type	ach (air changes per hour)
Preparation of material for application	PROC05	More than 4 hours	Enhanced (mechanical) room ventilation	5 - 10
Loading of application equipment and handling of coated parts before curing	PROC08a	More than 4 hours	Enhanced (mechanical) room ventilation	5 - 10
Professional application of coatings and inks by spraying	PROC11	More than 4 hours	Local exhaust ventilation	Refer to relevant technical standards
Film formation - force drying, stoving and other technologies	PROC04	More than 4 hours	Enhanced (mechanical) room ventilation	Refer to relevant technical standards
Cleaning	PROC05	More than 4 hours	Enhanced (mechanical) room ventilation	5 - 10
Waste management	PROC08a	More than 4 hours	Enhanced (mechanical) room ventilation	5 - 10

Contributing activity	Process category (ies)	Respiratory	Eye	Hands
Preparation of material for application	PROC05	None	Use eye protection according to EN ISO 16321.	Wear suitable gloves tested to EN374.
Loading of application equipment and handling of coated parts before curing	PROC08a	None	Use eye protection according to EN ISO 16321.	Wear suitable gloves tested to EN374.
Professional application of coatings and inks by spraying	PROC11	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10.	Use eye protection according to EN ISO 16321.	Wear suitable gloves tested to EN374.
Film formation - force drying, stoving and other technologies	PROC04	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10.	None	None
Cleaning	PROC05	None	Use eye protection according to EN ISO 16321.	Wear suitable gloves tested to EN374.
Waste management	PROC08a	None	Use eye protection according to EN ISO 16321.	Wear suitable gloves tested to EN374.

See section 8 of this Safety Data Sheet for specifications.



## **Disclaimer**

The information in this Safe Use of Mixture Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product.

No liability is accepted for any damage, no matter of what kind, which is direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.