

## GENERAL INFORMATION

Prospray A-497 2 Component Accelerator rapidly speeds up the dust free and drying times of Prospray clear coats, Prospray intermix Single Stage and all 2K Primers/Surfacers.

### MIXING RATIO



Add up to a maximum 20ml of A-497 2K Accelerator per 1 liter ready for use product.

### GUN SETUP



	NOZZLE (MM)	AIR PRESSURE (BAR / PSI)
HVLP	-	-
HE	-	-

Refer to the TDS of the A - component.

### APPLICATION



### FLASH-OFF AND DRY TIMES



	AIR DRY 20°C / 68°F		FORCED DRY 60°C / 140°F	
Flash off	-	-	Flash off	-
Dust free	-	-	Dust free	-
Dry to handle	-	-	Dry to handle	-
Dry to tape	-	-	Dry to tape	-
Dry to sand	-	-	Dry to sand	-
Dry to polish	-	-	Dry to polish	-



### SUBSTRATES



### POT LIFE AT 20°C (68°F)



When using A-497 2 Component Accelerator, pot life will be reduced.

### COMPONENTS



A-497 2 Component Accelerator should not be used in combination with ICA-690 Express Activator or ICA-802 M.S. Express Activator.

### ADDITIVES



### SURFACE PREPARATION



### NEXT LAYER



### PHYSICAL DATA



PHYSICAL DATA		
Chemical Base	Catalyst in solvents	
Physical Properties	Viscosity (RTS)	-
	Specific Gravity (kg/l)	0,89
	Flash Point Closed Cup	24°C / 75°F
	Volume % Solids	6,4
	Economy	-
	Gloss	-
	Colour	-

### PROTECTION



Use suitable respiratory protection (**we recommend the use of a fresh air supply respirator**).

For more detailed information please visit the following link for the Safety Data Sheet:

[sds.prospray.eu](https://sds.prospray.eu)

### CLEANUP



Clean equipment after use with a cleaning solvent.

**Dispose of solvent according to local regulations.**

### STORAGE / SHELF LIFE



Minimum 2 years; (Under normal storage conditions 10°C - 30°C / 50°F - 90°F) (unopened container).

### NOTES

