

GENERAL INFORMATION

BPS-050 1K NC Putty is a single component fine textured knifing filler designed to fill minor surface flaws, scratch marks and pinholes. It provides excellent adhesion to suitably prepared primer/surfacers and OEM finishes. 1K NC Putty may be applied with a squeegee or spreaders in 2-4 thin layers.

MIXING RATIO



Ready for use

GUN SETUP



N.A.

APPLICATION



2 - 4 coats

It is best to apply BPS-050 NC Putty with a filling knife, rubber or plastic spatula. One or more coats can be applied, depending on the desired thickness.

FLASH-OFF AND DRY TIMES



SUBSTRATES



Degreased and sanded old paint systems. Primed bare metal, sanded primer and OEM topcoat.

POT LIFE



N.A.

COMPONENTS



ADDITIVES



SURFACE PREPARATION



NEXT LAYER



Prospray Easy Sand HiFill Surfer:
A-400, A-402, A-404

PHYSICAL DATA



| PHYSICAL DATA | | |
|---------------------|---|-------------|
| Chemical Base | Combination of Nitro Cellulose and alkyd resins | |
| Physical Properties | Viscosity (RTS) | - |
| | Specific Gravity (kg/l) | 1,4 |
| | Flash Point Closed Cup | 25°C / 77°F |
| | Volume % Solids | 52% |
| | Economy | 25°C / 77°F |
| | Gloss | - |
| | Colour | Beige |

PROTECTION



Use suitable respiratory protection (**we recommend the use of a fresh air supply respirator**).

For more detailed information please visit the following link for the Safety Data Sheet:

sds.prospray.eu

CLEANUP



STORAGE / SHELF LIFE



Minimum 1 year; (Under normal storage conditions 10°C - 30°C / 50°F - 90°F) (unopened container).

NOTES



All reported product properties on the TDS are determined at a temperature of 30°C unless specified otherwise.