

## GENERAL INFORMATION

W820 Antistatic Degreaser standard Antistatic Degreaser.

### MIXING RATIO



### GUN SETUP



	NOZZLE (MM)	AIR PRESSURE (BAR / PSI)
HVLP	-	-
HE	-	-

### APPLICATION



### FLASH-OFF AND DRY TIMES



AIR DRY 20°C / 68°F		FORCED DRY 60°C / 140°F	
Flash off	-	Flash off	-
Dust free	-	Dust free	-
Dry to handle	-	Dry to handle	-
Dry to tape	-	Dry to tape	-
Dry to sand	-	Dry to sand	-
Dry to polish	-	Dry to polish	-



### SUBSTRATES



Bare Steel, old and new paint systems.

### POT LIFE AT 20°C (68°F)



### COMPONENTS



### ADDITIVES



### SURFACE PREPARATION



### NEXT LAYER



### PHYSICAL DATA



EU REGULATIONS		
VOC Code	2004/42/IIIB(a)(850)759	
Product sub category (according directive 2004/42/EC) and max VOC content (ISO 11890-1/2) of the ready to use product.	IIIB/a. Preparatory and cleaning - Preparatory. EU limit values: 850 g/l. (2007) This product contains a maximum of 759 g/l VOC.	
Chemical Base	Mix of organic solvents	
Physical Properties	Viscosity (RTS)	-
	Specific Gravity (kg/l)	0,76
	Flash Point Closed Cup	9°C / 48,2°F
	Volume % Solids	-
	Economy	-
	Gloss	-
	Colour	-

### PROTECTION



Use suitable respiratory protection (**we recommend the use of a fresh air supply respirator**).

For more detailed information please visit the following link for the Safety Data Sheet:

[sds.prospray.eu](https://sds.prospray.eu)

### CLEANUP



Dispose of solvent according to local regulations.

### STORAGE / SHELF LIFE



Minimum 2 years; (Under normal storage conditions 10°C - 30°C / 50°F - 90°F) (unopened container).

### NOTES

