


**6050 Putty White****APPLICATION DATA****Mixing Ratio**

: Add max. 3% (by weight) hardener.  
Never overdose!  
Mix thoroughly.

POTLIFE: 3-4 min 20 °C

**Drying time (min)****20°C**

: 20-30

**60°C Obj.**

: -

**Sanding**

: Dry sanding only.  
P80 -> P180 -> P280

**6050 Putty White****PRODUCT INFO**

- Area of application** : Putty for bodyworks, wood and polyester materials.
- Chemical base** : A filling 2 component thixotropic putty with high viscosity. Unsaturated polyester resin with special minerals.
- General qualities** : Putty for filling uneven areas and dents
- Auxiliary materials** : Special hardener (included).

<b>Physical properties</b>	<b>Specific gravity g/cm<sup>3</sup></b>	: 1.9
	<b>Flash point</b>	: Closed cup: 31°C (87.8°F)
	<b>Vol.% solids</b>	: -
	<b>Economy</b>	: -
	<b>Gloss</b>	:
	<b>Colour</b>	: White.

- Substrates** : Degreased and sanded: steel, wood and polyester glass fibre reinforced body parts
- Undercoats** : -
- Finishing materials** : Washprimers, Epoxy Primers, 2K/ MS/ HS Fillers
- Cleaning the equipment** : Gun Cleaner
- Storage life (years)** : 1  
(Under normal storage conditions and unopened tins).