

Product Information

Product Description:

AD690 Degreaser Solvent Based – This Silicone Remover (ready for use) should be used before applying paint products to clean contaminated surfaces.

Preparation:

For more detailed information go-to TI-Substrate and Pre-treatment on Color Retrieval System (CRS) or website www.valsparindustrialmix.com/emea/en/.

Substrates: Bare steel, metal objects, old and new cured paint systems.


Cleaning: Clean the Surface with AD690 Degreaser Solvent Based according “wipe on – wipe dry” technique.
 All surfaces must be dry and free from any contamination, e.g. oil, grease, release agents, before paint products are applied.

Physical properties:

| | |
|----------------------------|---|
| Chemical base | Mix of organic solvents |
| Density (kg/l) | 0,76 |
| Flash point | 9°C / 48,2°F |
| Pot life (+20°C) | - |
| Shelf life | Min. 24 month under normal storage conditions and unopened tins |
| Coverage (m ²) | - |
| Gloss | - |
| Color | Transparent |
| Temperature Stability | - |
| VOC (g/l) | Max. 759g/l see CRS (VOC: 2004/42/IIB(a)850g/l) |



Use suitable respiratory protection (air fed respirator strongly recommended).



Precautions: During application all health and safety measures referring to the use and handling of coating materials are to be observed, e. g. existing regulations issued by the trade associations in the Chemical Industry. For Health and Safety information please refer the Safety Datasheet (SDS). Information also available on our webpage: www.valsparindustrialmix.com/emea/en/

Note: The products listed are intended only for the professional user and for professional use. All recommendations given in writing on the use of our products to customers or users are not binding and do not give reasons for secondary obligations resulting from the bill of sale. Every care is taken to ensure that the technical information provided is accurate and up to date according to the present state of knowledge in science and our experience. These recommendations do not, however, exempt the customer from autonomously checking whether our products are suitable for the intend purpose. The durability of the coating system largely depends on the thorough preparation of the surface. Furthermore our uniform terms of delivery and payment are applicable.

With the publication of this Technical Data Sheet all previous versions regarding this product are no longer valid.