



## Safety Data Sheet

Revision Date 04-Jun-2018

Version 6

Supersedes Date: 07-Nov-2017

### Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product Identifier

**Product code** 303C01  
**Product name** VALSPAR 1K ACRYLIC BINDER 303C01

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Solvent rich paint

#### 1.3. Details of the supplier of the safety data sheet

*See section 16 for more information*

Valspar Corporation  
Level 4, 2 Burbank Place  
Baulkham Hills, New South Wales 2153

Valspar Corporation  
2-14 Patiki Road, Avondale 1026  
Auckland, New Zealand

For further information, please contact

**E-mail address** [sdshelpdesk@valspareurope.com](mailto:sdshelpdesk@valspareurope.com)

#### 1.4. Emergency telephone number

**Australia** +(61)-290372994  
**New Zealand** +(64)-98010034

**Poison control centre phone number**

**Australia** 13 11 26  
**New Zealand** 0800 764-766

### Section 2: HAZARDS IDENTIFICATION

#### GHS - Classification

Aspiration toxicity	Category 1
Skin Corrosion/Irritation	Category 2
Serious eye damage/eye irritation	Category 2
Reproductive Toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Acute aquatic toxicity	Category 2
Chronic Aquatic Toxicity	Category 2
Flammable liquids	Category 2

### Label elements



Signal word

**DANGER**

Contains Toluene, Butyl benzyl phthalate , Ethyl acetate, 1-Butanol

### HAZARD STATEMENTS

Highly flammable liquid and vapour  
 CAUSES SKIN IRRITATION  
 Causes serious eye irritation  
 May damage fertility or the unborn child  
 May cause drowsiness or dizziness  
 May cause damage to organs through prolonged or repeated exposure  
 Toxic to aquatic life with long lasting effects  
 May be fatal if swallowed and enters airways

### PREVENTION

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Wash face, hands and any exposed skin thoroughly after handling  
 Wear protective gloves  
 Wear eye/face protection  
 Use only outdoors or in a well-ventilated area  
 Do not breathe dust/fume/gas/mist/vapours/spray  
 Avoid release to the environment  
 P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ ventilating/ lighting/ equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep cool

### RESPONSE

IF exposed or concerned: Get medical advice/attention

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

#### Skin

IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash it before reuse

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

**INHALATION**

IF INHALED: Remove person to fresh air and keep comfortable for breathing

**INGESTION**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

**FIRE**

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Spill**

Collect spillage

**STORAGE**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

**DISPOSAL**

Dispose of contents/container to an approved waste disposal plant

**OTHER HAZARDS**

Not applicable

**Section 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical name	CAS No	Weight-%
Toluene	108-88-3	25 - 50
Ethyl acetate	141-78-6	10 - 25
Butyl benzyl phthalate	85-68-7	1 - 3
Cyclohexanone	108-94-1	1 - 3
1-Butanol	71-36-3	1 - 3
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	0.3 - 1
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega-hydroxy-	104810-48-2	0.1 - 0.3
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxoprop	104810-47-1	0.1 - 0.3
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidyl ester	82919-37-7	0.1 - 0.3

*If this section is blank, there are no hazardous components per NOHSC guidelines.*

**Section 4: FIRST AID MEASURES**

**4.1. Description of first aid measures**

**General Advice**

IF exposed or concerned: Get medical advice/attention.

**Eye Contact**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**Skin contact**

If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

**INHALATION**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

## INGESTION

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** None known.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Note to doctors** Treat symptomatically.

## Section 5: FIRE FIGHTING MEASURES

### 5.1. Extinguishing media

**Suitable Extinguishing Media** Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.

**Not to be used for safety reasons:** Strong water jet

### 5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitisation by skin contact.

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

**HAZCHEM Code:** 3YE

## Section 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

#### **Personal Precautions**

Avoid breathing vapours or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

#### **For emergency responders**

Use personal protection recommended in Section 8.

### 6.2. Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

### 6.3. Methods and material for containment and cleaning up

#### **Methods for Containment**

Prevent further leakage or spillage if safe to do so.

#### **Methods for Cleaning Up**

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labelled containers. Clean contaminated surface thoroughly. Take up mechanically, placing in appropriate containers for disposal.

### 6.4. Reference to other sections

See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment

information.

## Section 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

#### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

#### General hygiene considerations

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorised personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place.

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure Limits

If S\* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical name	Australia	New Zealand	ACGIH TLV
Toluene 108-88-3	TWA: 50 ppm TWA: 191 mg/m <sup>3</sup> STEL: 150 ppm STEL: 574 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 188 mg/m <sup>3</sup> S*	TWA: 20 ppm
Ethyl acetate 141-78-6	TWA: 200 ppm TWA: 720 mg/m <sup>3</sup> STEL: 400 ppm STEL: 1440 mg/m <sup>3</sup>	TWA: 200 ppm TWA: 720 mg/m <sup>3</sup>	TWA: 400 ppm
Butyl benzyl phthalate 85-68-7		TWA: 5 mg/m <sup>3</sup>	
Cyclohexanone 108-94-1	TWA: 25 ppm TWA: 100 mg/m <sup>3</sup>	TWA: 25 ppm TWA: 100 mg/m <sup>3</sup> S*	STEL: 50 ppm TWA: 20 ppm S*
1-Butanol 71-36-3	Peak: 50 ppm Peak: 152 mg/m <sup>3</sup>	Ceiling: 50 ppm Ceiling: 150 mg/m <sup>3</sup> S*	TWA: 20 ppm

### 8.2. Exposure controls

#### Engineering controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

#### Personal Protective Equipment

#### Eye/Face Protection

Tight sealing safety goggles.

### Skin and Body Protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing. Wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

### Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

### Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

### Thermal Protection

No information available

### Environmental exposure controls

Do not allow into any sewer, on the ground or into any body of water  
Local authorities should be advised if significant spillages cannot be contained

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Physical State	Liquid
Appearance	No information available
Odour	Solvent
Colour	Colourless
Odour threshold	No information available
PH	No information available
Melting point/freezing point	No information available
Boiling point / boiling range	77 °C / 171 °F
Flash Point	4 °C / 39 °F
Method	
Evaporation Rate	No information available
Flammability (solid, gas)	No information available
Flammability limit in air	
Upper flammability limit:	No information available
Lower flammability limit	No information available
Vapour pressure	No information available
Vapour Density	No information available
Specific gravity	0.942
Solubility(ies)	No information available
Partition coefficient	No information available
Autoignition Temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available
Explosive Properties	No information available
Oxidising Properties	No information available

### 9.2. Other information

Molecular Weight	No information available
------------------	--------------------------

## Section 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

#### **Hazardous polymerisation**

None under normal processing.

#### **Possibility of hazardous reactions**

None under normal processing.

### 10.4. Conditions to avoid

Heat, flames and sparks.

### 10.5. Incompatible materials

Strong oxidising agents.

### 10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

## **Section 11: TOXICOLOGICAL INFORMATION**

### Information on Toxicological Effects

#### Information on Likely Routes of Exposure

<b>Eye Contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	CAUSES SKIN IRRITATION.
<b>INGESTION</b>	May be fatal if swallowed and enters airways.
<b>INHALATION</b>	May cause drowsiness or dizziness.

#### Numerical Measures of Toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

<b>ATEmix (oral)</b>	25,773.00 Mg/kg
<b>ATEmix (inhalation-dust/mist)</b>	61.50 Mg/l
<b>ATEmix (inhalation-vapour)</b>	451.00 Mg/l

**UNKNOWN ACUTE TOXICITY** 0% of the mixture consists of ingredient(s) of unknown toxicity.

#### Numerical Measures of Toxicity - Component Information

<b>Chemical name</b>	<b>Oral LD50</b>	<b>Dermal LD50</b>	<b>Inhalation LC50</b>
Toluene 108-88-3	= 2600 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	= 12.5 mg/L ( Rat ) 4 h
Ethyl acetate 141-78-6	= 5620 mg/kg ( Rat )	> 20 mL/kg ( Rabbit ) > 18000 mg/kg ( Rabbit )	-
Butyl benzyl phthalate 85-68-7	= 2330 mg/kg ( Rat )	= 6700 mg/kg ( Rat )	> 6.7 mg/L ( Rat ) 4 h
Cyclohexanone 108-94-1	= 1544 mg/kg ( Rat )	= 947 mg/kg ( Rabbit )	= 8000 ppm ( Rat ) 4 h
1-Butanol 71-36-3	= 700 mg/kg ( Rat ) = 790 mg/kg ( Rat )	= 3402 mg/kg ( Rabbit ) = 3400 mg/kg ( Rabbit )	> 8000 ppm ( Rat ) 4 h
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate 41556-26-7	= 2615 mg/kg ( Rat )	-	-
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy- 104810-48-2	-	-	-
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)	-	-	-

l)-4-hydroxyphenyl]-1-oxoprop 104810-47-1			
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidiny ester 82919-37-7	-	-	-

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

<b>Skin Corrosion/Irritation</b>	CAUSES SKIN IRRITATION
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation
<b>Skin Sensitisation</b>	Not applicable
<b>Respiratory Sensitisation</b>	Not applicable
<b>Germ Cell Mutagenicity</b>	Not applicable
<b>Carcinogenicity</b>	Not applicable
<b>Reproductive toxicity</b>	May damage fertility or the unborn child
<b>Specific target organ toxicity (single exposure)</b>	May cause drowsiness or dizziness
<b>Specific target organ toxicity (repeated exposure)</b>	May cause damage to organs through prolonged or repeated exposure

**Toluene**  
Nervous System

**Aspiration Hazard**

May be fatal if swallowed and enters airways

**Section 12: ECOLOGICAL INFORMATION**

**Ecotoxicity** Toxic to aquatic life with long lasting effects

**Marine Pollutant** This material meets the definition of a marine pollutant

**Environmental Precautions** Prevent product from entering drains.

Chemical name	Algae/aquatic plants	Fish	Crustacea
Toluene 108-88-3	= 12.5 mg/L <i>Pseudokirchneriella subcapitata</i> 72 h EC50 > 433 mg/L <i>Pseudokirchneriella subcapitata</i> 96 h EC50	5.89 - 7.81 mg/L <i>Oncorhynchus mykiss</i> 96h LC50 14.1 - 17.16 mg/L <i>Oncorhynchus mykiss</i> 96h LC50 15.22 - 19.05 mg/L <i>Pimephales promelas</i> 96h LC50 11.0 - 15.0 mg/L <i>Lepomis macrochirus</i> 96h LC50 = 54 mg/L <i>Oryzias latipes</i> 96h LC50 = 28.2 mg/L <i>Poecilia reticulata</i> 96h LC50 50.87 - 70.34 mg/L <i>Poecilia reticulata</i> 96h LC50 = 12.6 mg/L <i>Pimephales promelas</i> 96h LC50 = 5.8 mg/L <i>Oncorhynchus mykiss</i> 96h LC50	= 11.5 mg/L <i>Daphnia magna</i> 48h EC50 5.46 - 9.83 mg/L <i>Daphnia magna</i> 48h EC50
Ethyl acetate 141-78-6	= 3300 mg/L <i>Desmodesmus subspicatus</i> 48 h EC50	220 - 250 mg/L <i>Pimephales promelas</i> 96h LC50 = 484 mg/L <i>Oncorhynchus mykiss</i> 96h LC50 352 - 500 mg/L <i>Oncorhynchus mykiss</i> 96h LC50	= 560 mg/L <i>Daphnia magna</i> 48h EC50
Butyl benzyl phthalate 85-68-7	0.2 - 28.2 mg/L <i>Pseudokirchneriella subcapitata</i> 72 h EC50 0.02 - 0.25 mg/L <i>Pseudokirchneriella subcapitata</i> 96 h EC50	1.39 - 3.88 mg/L <i>Pimephales promelas</i> 96h LC50 > 0.78 mg/L <i>Pimephales promelas</i> 96h LC50 1.0 - 10.0 mg/L <i>Lepomis macrochirus</i> 96h LC50 = 0.82 mg/L <i>Oncorhynchus mykiss</i> 96h LC50 1.0 - 10.0 mg/L <i>Oncorhynchus mykiss</i> 96h LC50	= 0.97 mg/L <i>Daphnia magna</i> 48h EC50 0.9 - 1.1 mg/L <i>Daphnia magna</i> 48h EC50 = 1.28 mg/L <i>Daphnia magna</i> 48h EC50 > 0.76 mg/L <i>Daphnia magna</i> 48h EC50

Cyclohexanone 108-94-1	= 20 mg/L <i>Chlorella vulgaris</i> 96 h EC50	481 - 578 mg/L <i>Pimephales promelas</i> 96h LC50 = 8.9 mg/L <i>Pimephales promelas</i> 96h LC50	= 800 mg/L <i>Daphnia magna</i> 24h EC50
1-Butanol 71-36-3	> 500 mg/L <i>Desmodesmus subspicatus</i> 96 h EC50 > 500 mg/L <i>Desmodesmus subspicatus</i> 72 h EC50	= 1740 mg/L <i>Pimephales promelas</i> 96h LC50 100000 - 500000 µg/L <i>Lepomis macrochirus</i> 96h LC50 = 1910000 µg/L <i>Pimephales promelas</i> 96h LC50 1730 - 1910 mg/L <i>Pimephales promelas</i> 96h LC50	= 1983 mg/L <i>Daphnia magna</i> 48h EC50 1897 - 2072 mg/L <i>Daphnia magna</i> 48h EC50
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate 41556-26-7		= 0.97 mg/L <i>Lepomis macrochirus</i> 96h LC50	= 20 mg/L <i>Daphnia magna</i> 24h EC50

**Persistence and Degradability** No information available.

**Bioaccumulation** No information available.

**Mobility** No information available.

Chemical name	Partition Coefficient (n-octanol/water)
Toluene 108-88-3	2.7
Ethyl acetate 141-78-6	0.6
Butyl benzyl phthalate 85-68-7	4.91
Cyclohexanone 108-94-1	0.86
1-Butanol 71-36-3	0.785
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate 41556-26-7	0.37

## Section 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste from Residues/Unused Products** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated Packaging** Improper disposal or reuse of this container may be dangerous and illegal. Empty containers must be scrapped or reconditioned.

## Section 14: TRANSPORT INFORMATION

<b>14.1 UN/ID no</b>	<b>IMDG</b> UN1263	<b>ADG</b> UN1263	<b>IATA</b> UN1263
<b>14.2 Proper Shipping Name</b>	Paint	Paint	Paint
<b>14.3 Hazard class</b>	3	3	3
<b>14.4 Packing group</b>	II	II	II
<b>14.5 Environmental hazard</b>	<b>Marine Pollutant</b> This material meets the definition of a marine pollutant		
	<b>Marine Pollutant</b> Butyl benzyl phthalate , Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate		
<b>14.6 Special Provisions</b>	163, 367 <b>EmS-No</b> F-E, S-E	163, 367	A3, A72, A192
<b>14.7 Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC CODE</b>	No information available		

HAZCHEM Code: 3YE

*The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.*

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### National Regulations

##### **Australia**

See section 8 for national exposure control parameters

##### **New Zealand**

See section 8 for national exposure control parameters

#### International Inventories

**AICS** - Australian Inventory of Chemical Substances

All components are listed or exempt from listing

**NZIoC** - New Zealand Inventory of Chemicals

Not all components are listed or exempt from listing

### 15.2. Chemical safety assessment

No information available

## Section 16: OTHER INFORMATION

#### **Supplier Address**

Valspar Automotive Australia Pty  
Limited  
Unit 11/8 Kerta Road  
Kincumber, NSW 2251  
Australia  
T: +612 43684054  
F: +612 43684215  
www.valsparautomotive.com.au

DBNZ Coatings Limited  
6 Killarney Lane  
Hamilton 3243  
New Zealand  
T: +64 7847 0933 F: +64 7847 0932  
E: info@dbnz.co.nz  
www.dbnzcoatings.co.nz

**Prepared by** Product Stewardship

**Revision Date** 04-Jun-2018

**Revision note** Not applicable.

#### **Disclaimer**

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. **UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.**

End of Safety Data Sheet