



Safety Data Sheet

Revision Date 04-Jun-2018

Version 5

Supersedes Date: 12-Dec-2016

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Product code 30MP

Product name 30MP VALSPAR MULTIPURPOSE THINNER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Paint remover, Solvents/thinner

1.3. Details of the supplier of the safety data sheet

See section 16 for more information

Valspar Corporation
Level 4, 2 Burbank Place
Baulkham Hills, New South Wales 2153

Valspar Corporation
2-14 Patiki Road, Avondale 1026
Auckland, New Zealand

For further information, please contact

E-mail address sdshelpdesk@valspareurope.com

1.4. Emergency telephone number

Australia +(61)-290372994
New Zealand +(64)-98010034

Poison control centre phone number

Australia 13 11 26
New Zealand 0800 764-766

Section 2: HAZARDS IDENTIFICATION

GHS - Classification

| | |
|--|------------|
| Aspiration toxicity | Category 1 |
| Acute toxicity - Dermal | Category 5 |
| Acute toxicity - Inhalation (Dusts/Mists) | Category 4 |
| Skin Corrosion/Irritation | Category 2 |
| Serious eye damage/eye irritation | Category 2 |
| Reproductive Toxicity | Category 2 |
| Specific target organ toxicity (single exposure) | Category 3 |
| Specific target organ toxicity (repeated exposure) | Category 2 |
| Chronic Aquatic Toxicity | Category 2 |
| Flammable liquids | Category 2 |

Label elements



Signal word

DANGER

Contains Xylenes (o-, m-, p- isomers), Solvent naphtha, petroleum, light aliphatic, Hexane, Ethylbenzene, Toluene, 2-Butoxyethanol, Acetone, Ethyl alcohol

HAZARD STATEMENTS

Highly flammable liquid and vapour
 May be harmful in contact with skin
 HARMFUL IF INHALED
 CAUSES SKIN IRRITATION
 Causes serious eye irritation
 Suspected of damaging fertility or the unborn child
 May cause drowsiness or dizziness
 May cause damage to organs through prolonged or repeated exposure
 Toxic to aquatic life with long lasting effects
 May be fatal if swallowed and enters airways
 May cause respiratory irritation

PREVENTION

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Wear protective gloves/protective clothing/eye protection/face protection
 Use only outdoors or in a well-ventilated area
 Wash face, hands and any exposed skin thoroughly after handling
 Wear protective gloves
 Wear eye/face protection
 Do not breathe dust/fume/gas/mist/vapours/spray
 Avoid release to the environment
 P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical/ ventilating/ lighting/ equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Keep cool

RESPONSE

IF exposed or concerned: Get medical advice/attention

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing

If eye irritation persists: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash it before reuse

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

INHALATION

IF INHALED: Remove person to fresh air and keep comfortable for breathing

INGESTION

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

FIRE

In case of fire: Use CO2, dry chemical, or foam for extinction

Spill

Collect spillage

STORAGE

Store locked up

Store in a well-ventilated place. Keep container tightly closed

DISPOSAL

Dispose of contents/container to an approved waste disposal plant

OTHER HAZARDS

Not applicable

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical name | CAS No | Weight-% |
|---|------------|----------|
| Xylenes (o-, m-, p- isomers) | 1330-20-7 | 25 - 50 |
| Acetone | 67-64-1 | 10 - 25 |
| Solvent naphtha, petroleum, light aliphatic | 64742-89-8 | 10 - 25 |
| Hexane | 110-54-3 | 5 - 10 |
| Ethyl alcohol | 64-17-5 | 5 - 10 |
| Ethylbenzene | 100-41-4 | 5 - 10 |
| 2-Butoxyethanol | 111-76-2 | 1 - 3 |
| Toluene | 108-88-3 | 1 - 3 |

If this section is blank, there are no hazardous components per NOHSC guidelines.

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice

IF exposed or concerned: Get medical advice/attention.

Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin contact

If skin irritation occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

INHALATION

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

INGESTION

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

Section 5: FIRE FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical, CO₂, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

HAZCHEM Code: 3YE

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal Precautions

Avoid breathing vapours or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

For emergency responders

Use personal protection recommended in Section 8.

6.2. Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Methods for Containment

Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labelled containers. Clean contaminated surface thoroughly.

6.4. Reference to other sections

See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

General hygiene considerations

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorised personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure Limits

If S* appears in the OEL table, it indicates this chemical contains a skin notation.

| Chemical name | Australia | New Zealand | ACGIH TLV |
|---|---|---|-------------------------------|
| Xylenes (o-, m-, p- isomers) 1330-20-7 | TWA: 80 ppm TWA: 350 mg/m ³ STEL: 150 ppm STEL: 655 mg/m ³ | TWA: 50 ppm TWA: 217 mg/m ³ | STEL: 150 ppm TWA: 100 ppm |
| Acetone 67-64-1 | TWA: 500 ppm TWA: 1185 mg/m ³ STEL: 1000 ppm STEL: 2375 mg/m ³ | TWA: 500 ppm TWA: 1185 mg/m ³ STEL: 1000 ppm STEL: 2375 mg/m ³ | STEL: 500 ppm TWA: 250 ppm |
| Hexane 110-54-3 | TWA: 20 ppm TWA: 72 mg/m ³ | TWA: 20 ppm TWA: 72 mg/m ³ | TWA: 50 ppm S* |
| Ethyl alcohol 64-17-5 | TWA: 1000 ppm TWA: 1880 mg/m ³ | TWA: 1000 ppm TWA: 1880 mg/m ³ | STEL: 1000 ppm |
| Ethylbenzene 100-41-4 | TWA: 100 ppm TWA: 434 mg/m ³ STEL: 125 ppm STEL: 543 mg/m ³ | TWA: 100 ppm TWA: 434 mg/m ³ STEL: 125 ppm STEL: 543 mg/m ³ | TWA: 20 ppm |
| 2-Butoxyethanol 111-76-2 | TWA: 20 ppm TWA: 96.9 mg/m ³ STEL: 50 ppm STEL: 242 mg/m ³ | TWA: 25 ppm TWA: 121 mg/m ³ S* | TWA: 20 ppm |
| Toluene 108-88-3 | TWA: 50 ppm TWA: 191 mg/m ³ STEL: 150 ppm STEL: 574 mg/m ³ | TWA: 50 ppm TWA: 188 mg/m ³ S* | TWA: 20 ppm |

Biological Limit Values:

| Chemical name | Australia | New Zealand |
|---|-----------|--|
| Xylenes (o-, m-, p- isomers) 1330-20-7 | | 1.5 g/L urine end of shift Methylhippuric acid |
| Acetone 67-64-1 | | 50 mg/L urine end of shift Acetone |
| Hexane 110-54-3 | | 5 mg/L urine end of shift 2,5-Hexanedione |

8.2. Exposure controls

Engineering controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Personal Protective Equipment

Eye/Face Protection

Wear safety glasses with side shields (or goggles).

Skin and Body Protection

Wear suitable protective clothing. Wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal Protection

No information available

Environmental exposure controls

Do not allow into any sewer, on the ground or into any body of water

Local authorities should be advised if significant spillages cannot be contained

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

| | |
|--------------------------------------|--------------------------|
| Physical State | Liquid |
| Appearance | No information available |
| Odour | Solvent |
| Colour | Clear |
| Odour threshold | No information available |
| PH | No information available |
| Melting point/freezing point | No information available |
| Boiling point / boiling range | 56.05 °C / 133 °F |
| Flash Point | -30 °C / -22 °F |
| Method | |
| Evaporation Rate | No information available |
| Flammability (solid, gas) | No information available |
| Flammability limit in air | |
| Upper flammability limit: | No information available |
| Lower flammability limit | No information available |
| Vapour pressure | No information available |
| Vapour Density | No information available |
| Specific gravity | 0.8 |
| Solubility(ies) | No information available |
| Partition coefficient | No information available |
| Autoignition Temperature | No information available |
| Decomposition temperature | No information available |
| Kinematic viscosity | No information available |
| Dynamic viscosity | No information available |
| Explosive Properties | No information available |
| Oxidising Properties | No information available |

9.2. Other information

| | |
|-------------------------|--------------------------|
| Molecular Weight | No information available |
|-------------------------|--------------------------|

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerisation

None under normal processing.

Possibility of hazardous reactions

None under normal processing.

10.4. Conditions to avoid

Heat, flames and sparks.

10.5. Incompatible materials

Strong oxidising agents.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide (CO₂).

Section 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Information on Likely Routes of Exposure

| | |
|---------------------|--|
| Eye Contact | Causes serious eye irritation. |
| Skin contact | May be harmful in contact with skin. CAUSES SKIN IRRITATION. |
| INGESTION | May be fatal if swallowed and enters airways. |
| INHALATION | May cause respiratory irritation. HARMFUL IF INHALED. May cause drowsiness or dizziness. |

Numerical Measures of Toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

| | |
|--------------------------------------|-----------------|
| ATEmix (oral) | 16,667.00 Mg/kg |
| ATEmix (dermal) | 3,548.00 Mg/kg |
| ATEmix (inhalation-dust/mist) | 4.00 Mg/l |
| ATEmix (inhalation-vapour) | 29.00 Mg/l |

UNKNOWN ACUTE TOXICITY 0% of the mixture consists of ingredient(s) of unknown toxicity.

Numerical Measures of Toxicity - Component Information

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|---|----------------------|---|---|
| Xylenes (o-, m-, p- isomers) 1330-20-7 | = 3500 mg/kg (Rat) | > 1700 mg/kg (Rabbit) > 4350 mg/kg (Rabbit) | = 5000 ppm (Rat) 4 h = 29.08 mg/L (Rat) 4 h |
| Acetone 67-64-1 | = 5800 mg/kg (Rat) | > 15700 mg/kg (Rabbit) | = 50100 mg/m ³ (Rat) 8 h |
| Solvent naphtha, petroleum, light aliphatic 64742-89-8 | - | = 3000 mg/kg (Rabbit) | - |
| Hexane 110-54-3 | = 25 g/kg (Rat) | = 3000 mg/kg (Rabbit) | = 48000 ppm (Rat) 4 h |
| Ethyl alcohol | = 7060 mg/kg (Rat) | - | = 124.7 mg/L (Rat) 4 h |

| | | | |
|-----------------------------|----------------------|--------------------------|-------------------------|
| 64-17-5 | | | |
| Ethylbenzene 100-41-4 | = 3500 mg/kg (Rat) | = 15400 mg/kg (Rabbit) | = 17.4 mg/L (Rat) 4 h |
| 2-Butoxyethanol 111-76-2 | = 470 mg/kg (Rat) | = 99 mg/kg (Rabbit) | = 450 ppm (Rat) 4 h |
| Toluene 108-88-3 | = 2600 mg/kg (Rat) | = 12000 mg/kg (Rabbit) | = 12.5 mg/L (Rat) 4 h |

Delayed and immediate effects as well as chronic effects from short and long-term exposure

| | |
|---|--|
| Skin Corrosion/Irritation | CAUSES SKIN IRRITATION |
| Serious eye damage/eye irritation | Causes serious eye irritation |
| Skin Sensitisation | Not applicable |
| Respiratory Sensitisation | Not applicable |
| Germ Cell Mutagenicity | Not applicable |
| Carcinogenicity | Not applicable |
| Reproductive toxicity | Suspected of damaging fertility or the unborn child |
| Specific target organ toxicity (single exposure) | May cause drowsiness or dizziness May cause respiratory irritation |
| Specific target organ toxicity (repeated exposure) | May cause damage to organs through prolonged or repeated exposure |
| Xylenes (o-, m-, p- isomers) <i>Kidney, Liver, Nervous System</i> | |
| Hexane <i>Nervous System</i> | |
| Ethylbenzene <i>Ears</i> | |
| Toluene <i>Nervous System</i> | |

Aspiration Hazard May be fatal if swallowed and enters airways

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity Toxic to aquatic life with long lasting effects

Marine Pollutant This material meets the definition of a marine pollutant

Environmental Precautions Prevent product from entering drains.

| Chemical name | Algae/aquatic plants | Fish | Crustacea |
|---|----------------------|--|--|
| Xylenes (o-, m-, p- isomers) 1330-20-7 | | > 780 mg/L <i>Cyprinus carpio</i> 96h LC50 = 780 mg/L <i>Cyprinus carpio</i> 96h LC50 23.53 - 29.97 mg/L <i>Pimephales promelas</i> 96h LC50 7.711 - 9.591 mg/L <i>Lepomis macrochirus</i> 96h LC50 = 19 mg/L <i>Lepomis macrochirus</i> 96h LC50 13.1 - 16.5 mg/L <i>Lepomis macrochirus</i> 96h LC50 13.5 - 17.3 mg/L <i>Oncorhynchus mykiss</i> 96h LC50 2.661 - 4.093 mg/L <i>Oncorhynchus mykiss</i> 96h LC50 = 13.4 mg/L <i>Pimephales promelas</i> 96h LC50 30.26 - 40.75 mg/L <i>Poecilia reticulata</i> 96h LC50 | = 3.82 mg/L water flea 48h EC50 = 0.6 mg/L <i>Gammarus lacustris</i> 48h LC50 |
| Acetone 67-64-1 | | 4.74 - 6.33 mg/L <i>Oncorhynchus mykiss</i> 96h LC50 6210 - 8120 mg/L <i>Pimephales promelas</i> 96h LC50 = 8300 mg/L <i>Lepomis macrochirus</i> | 12600 - 12700 mg/L <i>Daphnia magna</i> 48h EC50 10294 - 17704 mg/L <i>Daphnia magna</i> 48h EC50 |

| | | | |
|---|---|--|---|
| | | 96h LC50 | |
| Solvent naphtha, petroleum, light aliphatic 64742-89-8 | = 4700 mg/L <i>Pseudokirchneriella subcapitata</i> 72 h EC50 | | |
| Hexane 110-54-3 | | 2.1 - 2.98 mg/L <i>Pimephales promelas</i> 96h LC50 | > 1000 mg/L <i>Daphnia magna</i> 24h EC50 |
| Ethyl alcohol 64-17-5 | | > 100 mg/L <i>Pimephales promelas</i> 96h LC50 13400 - 15100 mg/L <i>Pimephales promelas</i> 96h LC50 12.0 - 16.0 mL/L <i>Oncorhynchus mykiss</i> 96h LC50 | = 10800 mg/L <i>Daphnia magna</i> 24h EC50 = 2 mg/L <i>Daphnia magna</i> 48h EC50 9268 - 14221 mg/L <i>Daphnia magna</i> 48h LC50 |
| Ethylbenzene 100-41-4 | 2.6 - 11.3 mg/L <i>Pseudokirchneriella subcapitata</i> 72 h EC50 = 4.6 mg/L <i>Pseudokirchneriella subcapitata</i> 72 h EC50 > 438 mg/L <i>Pseudokirchneriella subcapitata</i> 96 h EC50 1.7 - 7.6 mg/L <i>Pseudokirchneriella subcapitata</i> 96 h EC50 | 7.55 - 11 mg/L <i>Pimephales promelas</i> 96h LC50 = 4.2 mg/L <i>Oncorhynchus mykiss</i> 96h LC50 = 32 mg/L <i>Lepomis macrochirus</i> 96h LC50 11.0 - 18.0 mg/L <i>Oncorhynchus mykiss</i> 96h LC50 = 9.6 mg/L <i>Poecilia reticulata</i> 96h LC50 9.1 - 15.6 mg/L <i>Pimephales promelas</i> 96h LC50 | 1.8 - 2.4 mg/L <i>Daphnia magna</i> 48h EC50 |
| 2-Butoxyethanol 111-76-2 | | = 2950 mg/L <i>Lepomis macrochirus</i> 96h LC50 = 1490 mg/L <i>Lepomis macrochirus</i> 96h LC50 | 1698 - 1940 mg/L <i>Daphnia magna</i> 24h EC50 > 1000 mg/L <i>Daphnia magna</i> 48h EC50 |
| Toluene 108-88-3 | = 12.5 mg/L <i>Pseudokirchneriella subcapitata</i> 72 h EC50 > 433 mg/L <i>Pseudokirchneriella subcapitata</i> 96 h EC50 | 5.89 - 7.81 mg/L <i>Oncorhynchus mykiss</i> 96h LC50 14.1 - 17.16 mg/L <i>Oncorhynchus mykiss</i> 96h LC50 15.22 - 19.05 mg/L <i>Pimephales promelas</i> 96h LC50 11.0 - 15.0 mg/L <i>Lepomis macrochirus</i> 96h LC50 = 54 mg/L <i>Oryzias latipes</i> 96h LC50 = 28.2 mg/L <i>Poecilia reticulata</i> 96h LC50 50.87 - 70.34 mg/L <i>Poecilia reticulata</i> 96h LC50 = 12.6 mg/L <i>Pimephales promelas</i> 96h LC50 = 5.8 mg/L <i>Oncorhynchus mykiss</i> 96h LC50 | = 11.5 mg/L <i>Daphnia magna</i> 48h EC50 5.46 - 9.83 mg/L <i>Daphnia magna</i> 48h EC50 |

Persistence and Degradability No information available.

Bioaccumulation No information available.

Mobility No information available.

| Chemical name | Partition Coefficient (n-octanol/water) |
|---|---|
| Xylenes (o-, m-, p- isomers) 1330-20-7 | 3.15 |
| Acetone 67-64-1 | -0.24 |
| Ethyl alcohol 64-17-5 | -0.32 |
| Ethylbenzene 100-41-4 | 3.2 |
| 2-Butoxyethanol 111-76-2 | 0.81 |
| Toluene 108-88-3 | 2.7 |

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

| | |
|--|--|
| Waste from Residues/Unused Products | Disposal should be in accordance with applicable regional, national and local laws and regulations. |
| Contaminated Packaging | Improper disposal or reuse of this container may be dangerous and illegal. Empty containers must be scrapped or reconditioned. |

Section 14: TRANSPORT INFORMATION

| | <u>IMDG</u> | <u>ADG</u> | <u>IATA</u> |
|---|--|------------------------|--------------------------|
| 14.1 UN/ID no | UN1263 | UN1263 | UN1263 |
| 14.2 Proper Shipping Name | Paint related material | Paint related material | Paint related material |
| 14.3 Hazard class | 3 | 3 | 3 |
| 14.4 Packing group | II | II | II |
| 14.5 Environmental hazard | | | |
| Marine Pollutant | This material meets the definition of a marine pollutant | | |
| Marine Pollutant | Solvent naphtha, petroleum, light aliphatic , Hexane | | |
| 14.6 Special Provisions | 163, 367 | 163, * | A3, A72, A192 |
| | EmS-No F-E, S-E | | |
| 14.7 Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC CODE | | | No information available |
| HAZCHEM Code: | 3YE | | |

The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations

Australia

See section 8 for national exposure control parameters

New Zealand

See section 8 for national exposure control parameters

ERMA New Zealand HSNO approval code or group standard

HSR002650: SOLVENTS (FLAMMABLE)

International Inventories

AICS - Australian Inventory of Chemical Substances

All components are listed or exempt from listing

NZIoC - New Zealand Inventory of Chemicals

All components are listed or exempt from listing

15.2. Chemical safety assessment

No information available

Section 16: OTHER INFORMATION

Supplier Address

Valspar Automotive Australia Pty

Limited
Unit 11/8 Kerta Road
Kincumber, NSW 2251
Australia
T: +612 43684054
F: +612 43684215
www.valsparautomotive.com.au

DBNZ Coatings Limited
6 Killarney Lane
Hamilton 3243
New Zealand
T: +64 7847 0933 F: +64 7847 0932
E: info@dbnz.co.nz
www.dbnzcoatings.co.nz

Prepared by Product Stewardship

Revision Date 04-Jun-2018

Revision note Not applicable.

Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. **UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.**

End of Safety Data Sheet