



## Safety Data Sheet

Revision Date 04-Jun-2018

Version 8

Supersedes Date: 01-May-2017

### Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product Identifier

**Product code** AD4200  
**Product name** AIR DRY CLEAR COAT

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Paint, Coatings

#### 1.3. Details of the supplier of the safety data sheet

*See section 16 for more information*

Valspar Corporation  
Level 4, 2 Burbank Place  
Baulkham Hills, New South Wales 2153

Valspar Corporation  
2-14 Patiki Road, Avondale 1026  
Auckland, New Zealand

For further information, please contact

**E-mail address** [sdshelpdesk@valspar europe.com](mailto:sdshelpdesk@valspar europe.com)

#### 1.4. Emergency telephone number

**Australia** +(61)-290372994  
**New Zealand** +(64)-98010034

**Poison control centre phone number**

**Australia** 13 11 26  
**New Zealand** 0800 764-766

### Section 2: HAZARDS IDENTIFICATION

#### GHS - Classification

Acute toxicity - Oral	Category 5
Skin Corrosion/Irritation	Category 2
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Acute aquatic toxicity	Category 3
Chronic Aquatic Toxicity	Category 3
Flammable liquids	Category 2

## Label elements



**Signal word**

**DANGER**

Contains Dibutyltin dilaurate , Acetone, n-Butyl acetate, Benzene, 1-chloro-4-(trifluoromethyl)-, 2-Pentanone, 4-methyl-

### **HAZARD STATEMENTS**

Highly flammable liquid and vapour

May be harmful if swallowed

CAUSES SKIN IRRITATION

Causes serious eye irritation

May cause drowsiness or dizziness

Harmful to aquatic life with long lasting effects

AUH066 - Repeated exposure may cause skin dryness or cracking

### **PREVENTION**

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves

Wear eye/face protection

Avoid breathing dust/fume/gas/mist/vapours/spray

Use only outdoors or in a well-ventilated area

Avoid release to the environment

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ ventilating/ lighting/ equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

### **RESPONSE**

Call a POISON CENTER or doctor/physician if you feel unwell

#### **Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

#### **Skin**

IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash it before reuse

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

#### **INHALATION**

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

#### **INGESTION**

Do NOT induce vomiting  
IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

**FIRE**

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**STORAGE**

Store in a well-ventilated place. Keep container tightly closed  
Store locked up

**DISPOSAL**

Dispose of contents/container to an approved waste disposal plant

**OTHER HAZARDS**

Not applicable

**Section 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical name	CAS No	Weight-%
Acetone	67-64-1	10 - 25
n-Butyl acetate	123-86-4	10 - 25
Methyl n-amyl ketone	110-43-0	10 - 25
Benzene, 1-chloro-4-(trifluoromethyl)-	98-56-6	10 - 25
2-Pentanone, 4-methyl-	108-10-1	1 - 3
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy-	104810-48-2	0.3 - 1
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]	104810-47-1	0.3 - 1
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	0.3 - 1
Dibutyltin dilaurate	77-58-7	0.1 - 0.3
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester	82919-37-7	0.1 - 0.3

*If this section is blank, there are no hazardous components per NOHSC guidelines.*

**Section 4: FIRST AID MEASURES**

**4.1. Description of first aid measures**

**General Advice**

IF exposed or concerned: Get medical advice/attention.

**Eye Contact**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**Skin contact**

If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

**INHALATION**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

**INGESTION**

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

**4.2. Most important symptoms and effects, both acute and delayed**

**Symptoms** None known.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Note to doctors** Treat symptomatically.

## Section 5: FIRE FIGHTING MEASURES

### 5.1. Extinguishing media

**Suitable Extinguishing Media** Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.

**Not to be used for safety reasons:** Strong water jet

### 5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitisation by skin contact.

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

**HAZCHEM Code:** 3YE

## Section 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

#### **Personal Precautions**

Avoid breathing vapours or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

#### **For emergency responders**

Use personal protection recommended in Section 8.

### 6.2. Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

### 6.3. Methods and material for containment and cleaning up

#### **Methods for Containment**

Prevent further leakage or spillage if safe to do so.

#### **Methods for Cleaning Up**

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labelled containers. Clean contaminated surface thoroughly. Take up mechanically, placing in appropriate containers for disposal.

### 6.4. Reference to other sections

See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

## Section 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

### General hygiene considerations

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorised personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place.

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure Limits

If S\* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical name	Australia	New Zealand	ACGIH TLV
Acetone 67-64-1	TWA: 500 ppm TWA: 1185 mg/m <sup>3</sup> STEL: 1000 ppm STEL: 2375 mg/m <sup>3</sup>	TWA: 500 ppm TWA: 1185 mg/m <sup>3</sup> STEL: 1000 ppm STEL: 2375 mg/m <sup>3</sup>	STEL: 500 ppm TWA: 250 ppm
n-Butyl acetate 123-86-4	TWA: 150 ppm TWA: 713 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>	TWA: 150 ppm TWA: 713 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>	STEL: 150 ppm TWA: 50 ppm
Methyl n-amyl ketone 110-43-0	TWA: 50 ppm TWA: 233 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 233 mg/m <sup>3</sup>	TWA: 50 ppm
Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup> F
2-Pentanone, 4-methyl- 108-10-1	TWA: 50 ppm TWA: 205 mg/m <sup>3</sup> STEL: 75 ppm STEL: 307 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 205 mg/m <sup>3</sup> STEL: 75 ppm STEL: 307 mg/m <sup>3</sup>	STEL: 75 ppm TWA: 20 ppm
Dibutyltin dilaurate 77-58-7	TWA: 0.1 mg/m <sup>3</sup> STEL: 0.2 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup> STEL: 0.2 mg/m <sup>3</sup> S*	STEL: 0.2 mg/m <sup>3</sup> Sn TWA: 0.1 mg/m <sup>3</sup> Sn S*

#### Biological Limit Values:.

Chemical name	Australia	New Zealand
Acetone 67-64-1		50 mg/L urine end of shift Acetone
Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6		160 µmol/L urine prior to shift Fluoride 3 mg/L urine prior to shift Fluoride 530 µmol/L urine end of shift Fluoride 10 mg/L urine end of shift Fluoride
2-Pentanone, 4-methyl- 108-10-1		2 mg/L urine end of shift MIBK

### 8.2. Exposure controls

#### Engineering controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

## Personal Protective Equipment

### **Eye/Face Protection**

Tight sealing safety goggles.

### **Skin and Body Protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing. Wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

### **Hand protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

### **Respiratory Protection**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

### **Thermal Protection**

No information available

### **Environmental exposure controls**

Do not allow into any sewer, on the ground or into any body of water  
Local authorities should be advised if significant spillages cannot be contained

## **Section 9: PHYSICAL AND CHEMICAL PROPERTIES**

### 9.1. Information on basic physical and chemical properties

<b>Physical State</b>	Liquid
<b>Appearance</b>	No information available
<b>Odour</b>	Solvent
<b>Colour</b>	Clear
<b>Odour threshold</b>	No information available
<b>PH</b>	No information available
<b>Melting point/freezing point</b>	No information available
<b>Boiling point / boiling range</b>	56.05 °C / 133 °F
<b>Flash Point</b>	-9 °C / 16 °F
<b>Method</b>	
<b>Evaporation Rate</b>	No information available
<b>Flammability (solid, gas)</b>	No information available
<b>Flammability limit in air</b>	
<b>Upper flammability limit:</b>	No information available
<b>Lower flammability limit</b>	No information available
<b>Vapour pressure</b>	No information available
<b>Vapour Density</b>	No information available
<b>Specific gravity</b>	.96
<b>Solubility(ies)</b>	No information available
<b>Partition coefficient</b>	No information available
<b>Autoignition Temperature</b>	No information available
<b>Decomposition temperature</b>	No information available
<b>Kinematic viscosity</b>	No information available
<b>Dynamic viscosity</b>	No information available
<b>Explosive Properties</b>	No information available
<b>Oxidising Properties</b>	No information available

### 9.2. Other information

<b>Molecular Weight</b>	No information available
-------------------------	--------------------------

## **Section 10: STABILITY AND REACTIVITY**

### 10.1. Reactivity

No information available.

## **10.2. Chemical stability**

Stable under normal conditions.

## **10.3. Possibility of hazardous reactions**

### **Hazardous polymerisation**

None under normal processing.

### **Possibility of hazardous reactions**

None under normal processing.

## **10.4. Conditions to avoid**

Heat, flames and sparks.

## **10.5. Incompatible materials**

Strong oxidising agents.

## **10.6. Hazardous decomposition products**

Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Chlorine. Chlorine gas.

# **Section 11: TOXICOLOGICAL INFORMATION**

## **Information on Toxicological Effects**

### **Information on Likely Routes of Exposure**

<b>Eye Contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	CAUSES SKIN IRRITATION.
<b>INGESTION</b>	May be harmful if swallowed.
<b>INHALATION</b>	May cause drowsiness or dizziness.

### **Numerical Measures of Toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document

<b>ATEmix (oral)</b>	3,855.00 Mg/kg
<b>ATEmix (inhalation-dust/mist)</b>	9.60 Mg/l
<b>ATEmix (inhalation-vapour)</b>	71.00 Mg/l

**UNKNOWN ACUTE TOXICITY** 0% of the mixture consists of ingredient(s) of unknown toxicity.

### **Numerical Measures of Toxicity - Component Information**

<b>Chemical name</b>	<b>Oral LD50</b>	<b>Dermal LD50</b>	<b>Inhalation LC50</b>
Acetone 67-64-1	= 5800 mg/kg ( Rat )	> 15700 mg/kg ( Rabbit )	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
n-Butyl acetate 123-86-4	= 10768 mg/kg ( Rat )	> 17600 mg/kg ( Rabbit )	= 390 ppm ( Rat ) 4 h
Methyl n-amyl ketone 110-43-0	= 1600 mg/kg ( Rat ) = 1670 mg/kg ( Rat )	= 12600 µL/kg ( Rabbit ) = 12.6 mL/kg ( Rabbit )	2000 - 4000 ppm ( Rat ) 6 h
Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6	= 13 g/kg ( Rat )	> 2 mL/kg ( Rabbit )	= 33 mg/L ( Rat ) 4 h
2-Pentanone, 4-methyl- 108-10-1	= 2080 mg/kg ( Rat )	= 3000 mg/kg ( Rabbit )	= 8.2 mg/L ( Rat ) 4 h
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)- 5-(1,1-dimethylethyl)-4-hydroxyphen yl]-1-oxopropyl]-.omega.-hydroxy- 104810-48-2	-	-	-

Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)- 5-(1,1-dimethylethyl)-4-hydroxyphen yl]-1-oxopropyl]-.omega.-[3-[3-(2H-b enzotriazol-2-yl)-5-(1,1-dimethyleth yl)-4-hydroxyphenyl]-1-oxoprop 104810-47-1	-	-	-
Bis(1,2,2,6,6-pentamethyl-4-piperidy l) sebacate 41556-26-7	= 2615 mg/kg ( Rat )	-	-
Dibutyltin dilaurate 77-58-7	= 175 mg/kg ( Rat ) = 45 mg/kg ( Rat )	= 630 mg/kg ( Rabbit )	-
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester 82919-37-7	-	-	-

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Skin Corrosion/Irritation</b>	CAUSES SKIN IRRITATION
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation
<b>Skin Sensitisation</b>	Not applicable
<b>Respiratory Sensitisation</b>	Not applicable
<b>Germ Cell Mutagenicity</b>	Not applicable
<b>Carcinogenicity</b>	Not applicable
<b>Reproductive toxicity</b>	Not applicable
<b>Specific target organ toxicity (single exposure)</b>	May cause drowsiness or dizziness
Dibutyltin dilaurate Thymus	
<b>Specific target organ toxicity (repeated exposure)</b>	Not applicable
Dibutyltin dilaurate Thymus	

**Aspiration Hazard** Not applicable

## Section 12: ECOLOGICAL INFORMATION

**Ecotoxicity** Harmful to aquatic life with long lasting effects

**Environmental Precautions** Prevent product from entering drains.

Chemical name	Algae/aquatic plants	Fish	Crustacea
Acetone 67-64-1		4.74 - 6.33 mL/L <i>Oncorhynchus mykiss</i> 96h LC50 6210 - 8120 mg/L <i>Pimephales promelas</i> 96h LC50 = 8300 mg/L <i>Lepomis macrochirus</i> 96h LC50	12600 - 12700 mg/L <i>Daphnia magna</i> 48h EC50 10294 - 17704 mg/L <i>Daphnia magna</i> 48h EC50
n-Butyl acetate 123-86-4	= 674.7 mg/L <i>Desmodesmus subspicatus</i> 72 h EC50	= 62 mg/L <i>Leuciscus idus</i> 96h LC50 17 - 19 mg/L <i>Pimephales promelas</i> 96h LC50 = 100 mg/L <i>Lepomis macrochirus</i> 96h LC50	= 72.8 mg/L <i>Daphnia magna</i> 24h EC50
Methyl n-amyl ketone 110-43-0		126 - 137 mg/L <i>Pimephales promelas</i> 96h LC50	
Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6		11.5 - 15.8 mg/L <i>Lepomis macrochirus</i> 48h LC50	= 3.68 mg/L <i>Daphnia magna</i> 48h EC50
2-Pentanone, 4-methyl- 108-10-1	= 400 mg/L <i>Pseudokirchneriella subcapitata</i> 96 h EC50	496 - 514 mg/L <i>Pimephales promelas</i> 96h LC50	= 170 mg/L <i>Daphnia magna</i> 48h EC50
Bis(1,2,2,6,6-pentamethyl-4-piperidy l) sebacate 41556-26-7		= 0.97 mg/L <i>Lepomis macrochirus</i> 96h LC50	= 20 mg/L <i>Daphnia magna</i> 24h EC50
Dibutyltin dilaurate		= 2 mg/L <i>Oryzias latipes</i> 48h LC50	



77-58-7			
---------	--	--	--

**Persistence and Degradability** No information available.

**Bioaccumulation** No information available.

**Mobility** No information available.

Chemical name	Partition Coefficient (n-octanol/water)
Acetone 67-64-1	-0.24
n-Butyl acetate 123-86-4	1.81
Methyl n-amyl ketone 110-43-0	1.98
Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6	3.7
2-Pentanone, 4-methyl- 108-10-1	1.19
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate 41556-26-7	0.37

## Section 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste from Residues/Unused Products** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated Packaging** Improper disposal or reuse of this container may be dangerous and illegal. Empty containers must be scrapped or reconditioned.

## Section 14: TRANSPORT INFORMATION

<b>14.1 UN/ID no</b>	<b>IMDG</b> UN1263	<b>ADG</b> UN1263	<b>IATA</b> UN1263
<b>14.2 Proper Shipping Name</b>	Paint	Paint	Paint
<b>14.3 Hazard class</b>	3	3	3
<b>14.4 Packing group</b>	II	II	II
<b>14.5 Environmental hazard</b>			
<b>14.6 Special Provisions</b>	163, 367 <b>EmS-No</b> F-E, S-E	163, *	A3, A72, A192
<b>14.7 Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC CODE</b>			No information available
<b>HAZCHEM Code:</b>	3YE		

*The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.*

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### National Regulations

##### Australia

See section 8 for national exposure control parameters

## New Zealand

See section 8 for national exposure control parameters

### ERMA New Zealand HSNO approval code or group standard

HSR002662: SURFACE COATINGS AND COLOURANTS (FLAMMABLE)

### International Inventories

**AICS** - Australian Inventory of Chemical Substances

Not all components are listed or exempt from listing

**NZIoC** - New Zealand Inventory of Chemicals

All components are listed or exempt from listing

### 15.2. Chemical safety assessment

No information available

## Section 16: OTHER INFORMATION

### Supplier Address

Valspar Automotive Australia Pty  
Limited  
Unit 11/8 Kerta Road  
Kincumber, NSW 2251  
Australia  
T: +612 43684054  
F: +612 43684215  
www.valsparautomotive.com.au

DBNZ Coatings Limited  
6 Killarney Lane  
Hamilton 3243  
New Zealand  
T: +64 7847 0933 F: +64 7847 0932  
E: info@dbnz.co.nz  
www.dbnzcoatings.co.nz

**Prepared by** Product Stewardship

**Revision Date** 04-Jun-2018

**Revision note** Not applicable.

### Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. **UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.**

End of Safety Data Sheet