

# Safety Data Sheet

Revision Date 09-Oct-2020

Version 15

Supersedes Date: 12-Aug-2019

## Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product Identifier

**Product code** HPC400  
**Product name** AIR CURE ACTIVATOR SLOW

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Paint, Coatings

### 1.3. Details of the supplier of the safety data sheet

*See section 16 for more information*

Valspar Corporation  
Level 4, 2 Burbank Place  
Baulkham Hills, New South Wales 2153

Valspar Corporation  
2-14 Patiki Road, Avondale 1026  
Auckland, New Zealand

For further information, please contact

**E-mail address** [sdshelpdesk@valspareurope.com](mailto:sdshelpdesk@valspareurope.com)

### 1.4. Emergency telephone number

**Australia** +(61)-290372994  
**New Zealand** +(64)-98010034

### Poison control centre phone number

**Australia** 13 11 26  
**New Zealand** 0800 764-766

## Section 2: HAZARDS IDENTIFICATION

### GHS - Classification

Aspiration toxicity	Category 1
Acute toxicity - Oral	Category 5
Acute toxicity - Inhalation (Vapours)	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin Corrosion/Irritation	Category 2
Respiratory Sensitisation	Category 1
Skin Sensitisation	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Acute aquatic toxicity	Category 3
Chronic Aquatic Toxicity	Category 2
Flammable liquids	Category 3

## Label elements



Signal word

**DANGER**

Contains Solvent naphtha, petroleum, heavy aromatic, Solvent naphtha, petroleum, light aromatic, Benzene, trimethyl-, 1,3,5-Trimethylbenzene , Hexamethylene diisocyanate homopolymer

### **HAZARD STATEMENTS**

Flammable liquid and vapour

May be harmful if swallowed

HARMFUL IF INHALED

CAUSES SKIN IRRITATION

May cause allergy or asthma symptoms or breathing difficulties if inhaled

May cause an allergic skin reaction

Suspected of causing cancer

May cause respiratory irritation

Harmful to aquatic life

Toxic to aquatic life with long lasting effects

May be fatal if swallowed and enters airways

### **PREVENTION**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapours/spray

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves

In case of inadequate ventilation wear respiratory protection

Contaminated work clothing should not be allowed out of the workplace

Avoid release to the environment

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ ventilating/ lighting/ equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

### **RESPONSE**

IF exposed or concerned: Get medical advice/attention

#### **Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

#### **Skin**

IF ON SKIN: Wash with plenty of soap and water

Take off contaminated clothing and wash it before reuse

If skin irritation or rash occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

#### **INHALATION**

IF INHALED: Remove person to fresh air and keep comfortable for breathing

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician

#### **INGESTION**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

**FIRE**

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Spill**

Collect spillage

**STORAGE**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

**DISPOSAL**

Dispose of contents/container to an approved waste disposal plant

**OTHER HAZARDS**

Not applicable

**Section 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical name	CAS No	Weight-%
Hexamethylene diisocyanate homopolymer	28182-81-2	50 - 70
Solvent naphtha, petroleum, heavy aromatic	64742-94-5	10 - 25
Methyl n-amyl ketone	110-43-0	10 - 25
Cyclohexane, 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethyl-, homopolymer	53880-05-0	3 - 5
Solvent naphtha, petroleum, light aromatic	64742-95-6	3 - 5
Ethylene glycol monobutyl ether acetate	112-07-2	1 - 3
Naphthalene	91-20-3	1 - 3
Benzene, trimethyl-	25551-13-7	1 - 3
Hexamethylene diisocyanate	822-06-0	0.1 - 0.3

*If this section is blank, there are no hazardous components per NOHSC guidelines.*

**Section 4: FIRST AID MEASURES**

**4.1. Description of first aid measures**

**General Advice**

IF exposed or concerned: Get medical advice/attention.

**Eye Contact**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**Skin contact**

If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

**INHALATION**

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

**INGESTION**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

**Symptoms**

None known.

**4.3. Indication of any immediate medical attention and special treatment needed**

**Note to doctors**

Treat symptomatically.

## Section 5: FIRE FIGHTING MEASURES

### 5.1. Extinguishing media

**Suitable Extinguishing Media** Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.

**Not to be used for safety reasons:** Strong water jet

### 5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitisation by inhalation. May cause sensitisation by skin contact.

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

**HAZCHEM Code:** 3Y

## Section 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

#### **Personal Precautions**

Avoid breathing vapours or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

#### **For emergency responders**

Use personal protection recommended in Section 8.

### 6.2. Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

### 6.3. Methods and material for containment and cleaning up

#### **Methods for Containment**

Prevent further leakage or spillage if safe to do so.

#### **Methods for Cleaning Up**

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Take up mechanically, placing in appropriate containers for disposal. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labelled containers. Clean contaminated surface thoroughly.

### 6.4. Reference to other sections

See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

## Section 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

#### **General Advice**

Persons with a history of asthma, allergies, chronic or recurrent respiratory disease should not be exposed to any process in which this product is used. Examination of lung function should be carried out on a regular basis on persons spraying this product. This product contains isocyanates. Isocyanates are known to be strong sensitisers. Persons already sensitised to diisocyanates may

develop allergic reactions when using this product.

#### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

#### General hygiene considerations

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorised personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place.

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure Limits

If S\* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical name	Australia	New Zealand	ACGIH TLV
Methyl n-amyl ketone 110-43-0	TWA: 50 ppm TWA: 233 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 233 mg/m <sup>3</sup>	TWA: 50 ppm
Ethylene glycol monobutyl ether acetate 112-07-2	TWA: 20 ppm TWA: 133 mg/m <sup>3</sup> STEL: 50 ppm STEL: 333 mg/m <sup>3</sup>		TWA: 20 ppm
Naphthalene 91-20-3	TWA: 10 ppm TWA: 52 mg/m <sup>3</sup> STEL: 15 ppm STEL: 79 mg/m <sup>3</sup>	TWA: 10 ppm TWA: 52 mg/m <sup>3</sup> STEL: 15 ppm STEL: 79 mg/m <sup>3</sup>	TWA: 10 ppm S*
Benzene, trimethyl- 25551-13-7	TWA: 25 ppm TWA: 123 mg/m <sup>3</sup>	TWA: 25 ppm TWA: 123 mg/m <sup>3</sup>	TWA: 25 ppm
Hexamethylene diisocyanate 822-06-0	TWA: 0.02 mg/m <sup>3</sup> STEL: 0.07 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup> dust, mist or vapours STEL: 0.07 mg/m <sup>3</sup> dust, mist or vapour	TWA: 0.005 ppm

### 8.2. Exposure controls

#### Engineering controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Under cool dry conditions, it is possible for the isocyanate to remain unreacted in the paint film for up to 30 hours after application. If dry flatting is unavoidable air fed respiratory protective equipment should be used.

#### Personal Protective Equipment

#### Eye/Face Protection

Tight sealing safety goggles.

### Skin and Body Protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing. Wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

### Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

### Respiratory Protection

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

### Thermal Protection

No information available

### Environmental exposure controls

Do not allow into any sewer, on the ground or into any body of water  
Local authorities should be advised if significant spillages cannot be contained

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Physical State	Liquid
Appearance	No information available
Odour	Solvent
Colour	Clear
Odour threshold	No information available
PH	No information available
Melting point/freezing point	No information available
Boiling point / boiling range	No information available °C / °F
Flash Point	27 °C / 81 °F
Method	
Evaporation Rate	No information available
Flammability (solid, gas)	No information available
Flammability limit in air	
Upper flammability limit:	No information available
Lower flammability limit	No information available
Vapour pressure	No information available
Vapour Density	No information available
Specific gravity	1.03
Solubility(ies)	No information available
Partition coefficient	No information available
Autoignition Temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available
Explosive Properties	No information available
Oxidising Properties	No information available

### 9.2. Other information

Molecular Weight No information available

## Section 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

#### **Hazardous polymerisation**

None under normal processing.

#### **Possibility of hazardous reactions**

None under normal processing.

### 10.4. Conditions to avoid

Heat, flames and sparks.

### 10.5. Incompatible materials

Strong oxidising agents.

### 10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

## Section 11: TOXICOLOGICAL INFORMATION

### Information on Toxicological Effects

#### Information on Likely Routes of Exposure

#### **Eye Contact**

Not applicable.

#### **Skin contact**

CAUSES SKIN IRRITATION. May cause an allergic skin reaction.

#### **INGESTION**

May be harmful if swallowed. May be fatal if swallowed and enters airways.

#### **INHALATION**

May cause respiratory irritation. HARMFUL IF INHALED. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

### Numerical Measures of Toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

<b>ATEmix (oral)</b>	4,347.00 Mg/kg
<b>ATEmix (dermal)</b>	52,566.00 Mg/kg
<b>ATEmix (inhalation-dust/mist)</b>	2.00 Mg/l
<b>ATEmix (inhalation-vapour)</b>	15.00 Mg/l

**UNKNOWN ACUTE TOXICITY** 0% of the mixture consists of ingredient(s) of unknown toxicity.

### Numerical Measures of Toxicity - Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hexamethylene diisocyanate homopolymer 28182-81-2	-	-	= 18500 mg/m <sup>3</sup> ( Rat ) 1 h
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	> 5000 mg/kg ( Rat )	> 2 mL/kg ( Rabbit )	> 590 mg/m <sup>3</sup> ( Rat ) 4 h
Methyl n-amyl ketone 110-43-0	= 1600 mg/kg ( Rat ) = 1670 mg/kg ( Rat )	= 12600 µL/kg ( Rabbit ) = 12.6 mL/kg ( Rabbit )	2000 - 4000 ppm ( Rat ) 6 h
Cyclohexane, 5-isocyanato-1-(isocyanatomethyl)- 1,3,3-trimethyl-, homopolymer 53880-05-0	-	-	-
Solvent naphtha, petroleum, light aromatic 64742-95-6	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h
Ethylene glycol monobutyl ether acetate 112-07-2	= 2400 mg/kg ( Rat )	= 1500 mg/kg ( Rabbit )	> 400 ppm ( Rat ) 4 h
Naphthalene	= 490 mg/kg ( Rat ) = 1110 mg/kg ( Rat )	(> 20 g/kg ( Rabbit ) = 1120 mg/kg ( Rat )	> 340 mg/m <sup>3</sup> ( Rat ) 1 h

91-20-3	Rat )	Rabbit )	
Benzene, trimethyl- 25551-13-7	= 8970 mg/kg ( Rat )	-	-
Hexamethylene diisocyanate 822-06-0	= 710 µL/kg ( Rat )	= 593 mg/kg ( Rabbit )	= 0.06 mg/L ( Rat ) 4 h

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

<b>Skin Corrosion/Irritation</b>	CAUSES SKIN IRRITATION
<b>Serious eye damage/eye irritation</b>	Not applicable
<b>Skin Sensitisation</b>	May cause an allergic skin reaction
<b>Respiratory Sensitisation</b>	May cause allergy or asthma symptoms or breathing difficulties if inhaled
<b>Germ Cell Mutagenicity</b>	Not applicable
<b>Carcinogenicity</b>	Suspected of causing cancer
<b>Reproductive toxicity</b>	Not applicable
<b>Specific target organ toxicity (single exposure)</b>	May cause respiratory irritation
<b>Specific target organ toxicity (repeated exposure)</b>	Not applicable
<b>Aspiration Hazard</b>	May be fatal if swallowed and enters airways

**Section 12: ECOLOGICAL INFORMATION**

**Ecotoxicity** Harmful to aquatic life Toxic to aquatic life with long lasting effects

**Marine Pollutant** This material meets the definition of a marine pollutant

**Environmental Precautions** Prevent product from entering drains.

Chemical name	Algae/aquatic plants	Fish	Crustacea
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	= 2.5 mg/L <i>Skeletonema costatum</i> 72 h EC50	= 45 mg/L <i>Pimephales promelas</i> 96h LC50 = 41 mg/L <i>Pimephales promelas</i> 96h LC50 = 1740 mg/L <i>Lepomis macrochirus</i> 96h LC50 = 19 mg/L <i>Pimephales promelas</i> 96h LC50 = 2.34 mg/L <i>Oncorhynchus mykiss</i> 96h LC50	= 0.95 mg/L <i>Daphnia magna</i> 48h EC50
Methyl n-amyl ketone 110-43-0		126 - 137 mg/L <i>Pimephales promelas</i> 96h LC50	
Solvent naphtha, petroleum, light aromatic 64742-95-6		= 9.22 mg/L <i>Oncorhynchus mykiss</i> 96h LC50	= 6.14 mg/L <i>Daphnia magna</i> 48h EC50
Ethylene glycol monobutyl ether acetate 112-07-2	> 500 mg/L <i>Desmodesmus subspicatus</i> 72 h EC50		= 37 mg/L <i>Daphnia magna</i> 48h EC50
Naphthalene 91-20-3	= 0.4 mg/L <i>Skeletonema costatum</i> 72 h EC50	= 31.0265 mg/L <i>Lepomis macrochirus</i> 96h LC50 = 1.99 mg/L <i>Pimephales promelas</i> 96h LC50 0.91 - 2.82 mg/L <i>Oncorhynchus mykiss</i> 96h LC50 = 1.6 mg/L <i>Oncorhynchus mykiss</i> 96h LC50 5.74 - 6.44 mg/L <i>Pimephales promelas</i> 96h LC50	1.09 - 3.4 mg/L <i>Daphnia magna</i> 48h EC50 = 1.96 mg/L <i>Daphnia magna</i> 48h EC50 = 2.16 mg/L <i>Daphnia magna</i> 48h LC50
Benzene, trimethyl- 25551-13-7		= 7.72 mg/L <i>Pimephales promelas</i> 96h LC50	
Hexamethylene diisocyanate 822-06-0		= 26.1 mg/L <i>Brachydanio rerio</i> 96h LC50	



**Persistence and Degradability** No information available.

**Bioaccumulation** No information available.

**Mobility** No information available.

Chemical name	Partition Coefficient (n-octanol/water)
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	6.1
Methyl n-aryl ketone 110-43-0	1.98
Ethylene glycol monobutyl ether acetate 112-07-2	1.51
Naphthalene 91-20-3	3.6

## Section 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste from Residues/Unused Products** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated Packaging** Improper disposal or reuse of this container may be dangerous and illegal. Empty containers must be scrapped or reconditioned.

## Section 14: TRANSPORT INFORMATION

<b>14.1 UN/ID no</b>	<b>IMDG</b> UN1263	<b>ADG</b> UN1263	<b>IATA</b> UN1263
<b>14.2 Proper Shipping Name</b>	Paint	Paint	Paint
<b>14.3 Hazard class</b>	3	3	3
<b>14.4 Packing group</b>	III	III	III
<b>14.5 Environmental hazard</b>			
<b>Marine Pollutant</b>	This material meets the definition of a marine pollutant		
<b>Marine Pollutant</b>	Solvent naphtha, petroleum, heavy aromatic , Solvent naphtha, petroleum, light aromatic		
<b>14.6 Special Provisions</b>	163, 223, 367 955	163, 223, 367	A3, A72, A192
	<b>EmS-No</b> F-E, S-E		
<b>14.7 Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC CODE</b>			No information available
<b>HAZCHEM Code:</b>	3Y		

*The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.*

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### National Regulations

##### Australia

See section 8 for national exposure control parameters

##### New Zealand

See section 8 for national exposure control parameters

ERMA New Zealand HSNO approval code or group standard

**International Inventories**

**AICS** - Australian Inventory of Chemical Substances

All components are listed or exempt from listing

**NZIoC** - New Zealand Inventory of Chemicals

All components are listed or exempt from listing

**15.2. Chemical safety assessment**

No information available

**Section 16: OTHER INFORMATION**

**Supplier Address**

Valspar Automotive Australia Pty  
Limited  
Unit 11/8 Kerta Road  
Kincumber, NSW 2251  
Australia  
T: +612 43684054  
F: +612 43684215  
www.valsparautomotive.com.au

DBNZ Coatings Limited  
6 Killarney Lane  
Hamilton 3243  
New Zealand  
T: +64 7847 0944 F: +64 7847 0932  
E: info@dbnz.co.nz  
www.dbnzcoatings.co.nz

**Prepared by** Product Stewardship

**Revision Date** 09-Oct-2020

**Revision note** Not applicable.

**Disclaimer**

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. **UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.**

End of Safety Data Sheet