

Plastic Cleaner



GENERAL INFORMATION

PR1 Plastic Cleaner removes mold release agents and other surface contaminants from plastics. PR1 must be used prior to application of PR2 Plastic Adhesion Promoter.



COMPONENTS

Plastic Cleaner



2. MIXING RATIO

· Ready to Use



POT LIFE

N/A



4. CLEAN UP

N/A



5. ADDITIVES



6. SURFACE PREPARATION



7. TOPCOATS



8. TECH NOTES



9. SUBSTRATES

- Commonly used automotive interior and exterior plastics
- TPO Thermopolyolefin
- RIM Reaction Injected Molded Polyurethane
- PVC Polyvinyl Chloride
- PPO Polypropylene



10. APPLICATION

- · Clean surface with PR1 and wipe dry with clean cloth before product evaporates
- Scuff surface with P600 grit wet or dry sandpaper or gray/yellow scuff pad
- Re-clean surface with PR1 and wipe dry with clean cloth before product
- Use PR2 Plastic Adhesion Promoter as required (See PR2 Data Sheet) NOTE: Tempering before cleaning will help to remove mold release agent



11. FLASH/DRY TIMES



12. INFRARED CURE



13. GUN SET-UP

• N/A



14. PHYSICAL DATA

FOR USA/Canada (Actual VOC Compliance)

RTS REGULATORY DATA:	PR1	
	(AS IS)	
	LBS./GAL	g/L
Actual VOC	0.2 Max.	25 Max.
Density	8 - 10	960 - 1200
	WT.%	VOL.%
Total Solids Content	0	0
Total Volatile Content	100	100
Water	97 - 99	97 - 99
Exempt Compound Content	0	0
Coating Category	Surface Cleaner	

NOTE: US/Canadian Regulations allow for the use of exempt compounds for VOC calculations.

FOR REST-OF-WORLD (outside US and Canada):

	PR1	
RTS REGULATORY DATA:	(AS IS)	
	LBS./GAL	g/L
VOC	0.2 Max	25 Max
Density	8 - 10	960 - 1200
	WT%	VOL%
Total Solids Content	0	0
Total Volatile Content	100	100
Water	97 - 99	97 - 99
Coating Category	Surface Cleaner	

NOTES

If used as instructed, this product is designed to comply with VOC standards in low-VOC jurisdictions. Confirm compliance with state and local air quality rules before use. The data on In used as instructed, this product is designed to comply with VOC standards in low-VOC jurisdictions. Confirm compliance with state and local air quality rules before use. The data of this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.